

Basic Rack PDU


Overview

The American Power Conversion® Basic Rack PDU distributes power to devices in the rack.

Outlets. The Rack PDU has twenty-four NEMA 5-20 outlets.

Power cord. The 10-foot (3.05-meter) power cord terminates with a NEMA L5-30 connector.

AP7532





Specifications

Electrical	
Input connector	NEMA L5-30 plug
Output connectors	24-NEMA 5-20 outlets
Nominal input voltage	120 VAC
Acceptable input voltage	\pm 10% of normal voltage
Input frequency	50/60 Hz
Physical	
Size $(H \times W \times D)$	63.75 x 2.19 x 1.73 in (161.92 x 5.56 x 4.39 cm)
Shipping Dimensions $(H \times W \times D)$	84.00 x 6.00 x 5.00 in (213.36 x 15.24 x 12.7 cm)
Weight	12.25 lb (5.56 kg)
Shipping weight	14.25 lb (6.46 kg)
Environmental	
Elevation (above MSL)	
Operating Storage	0-15,000 ft (0-4500 m) 0-50,000 ft (0-15 000 m)
Temperature Operating Storage	23 to 115° F (-5 to 45° C) -13 to 149° F (-25 to 65° C)
Humidity Operating Storage	5–95% RH non-condensing 5–95% RH non-condensing
Compliance	
Safety verification	UL, cUL 60950

Customer support and warranty information is available at the APC Web site, www.apc.com.

© 2008 American Power Conversion. All rights reserved. All APC trademarks are property of American Power Conversion. Other trademarks are property of their respective owners.



990-1893A 11/2008