



AP8959

★★★★★ 5.0 (2) [Write a review](#)



APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power...

Includes: Installation guide, Rack Mounting brackets, Safety guide, Serial configuration cable

Technical Specifications

Output

Nominal Output Voltage	100V, 200V, 208V, 230V
Overload Protection	No
Maximum Total Current Draw	16
Output Connections	(3) IEC 320 C19 (Battery Backup) (21) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC-320 C20
Acceptable Input Voltage	100-240VAC
Load Capacity	3300VA
Maximum Input Current	20A
Regulatory Derated Input Current (North America)	16A

Physical

Maximum Height	70.5inches (1791MM, 179.1CM)
Maximum Width	2.2inches (56MM, 5.6CM)
Maximum Depth	1.82inches (46MM, 4.6CM)
Net Weight	12.6lbs. (5.73KG)
Shipping weight	17.3lbs. (7.86KG)
Shipping Height	78.8inches (2002MM, 200.2CM)
Shipping Width	6.5inches (165MM, 16.5CM)
Shipping Depth	4.5inches (114MM, 11.4CM)
Color	Black
Units per Pallet	48.0

Environmental

Operating Temperature	23 - 113 °F (-5 - 45 °C)
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-50000ft (0-15000meters)

Conformance

Approvals	cUL Listed, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Class A, ICES-003, PSE, UL Listed, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab
Battery Directive	Compliant