



PE76

★★★★★ 4.9 (12) [Write a review](#)



Basic Protection Against Power Surges for Computers and Electronics

Includes: User Manual

Technical Specifications

Output

Number of Outlets	7.0
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	6ft (1.83meters)
Number of Power Cords	1
Maximum Input Current	15.0A
Maximum Line Current	15A

Surge Protection and Filtering

Surge energy rating	1440Joules
ts_nm_surge_response	1ns
Peak Current Common Mode	56kAmps
Peak Current Normal Mode	28kAmps

Physical

Maximum Height	1.18inches (30MM, 3.0CM)
Maximum Width	2.05inches (52MM, 5.2CM)
Maximum Depth	13.7inches (348MM, 34.8CM)
Net Weight	1.21lbs. (0.55KG)
Shipping weight	1.43lbs. (0.65KG)
Shipping Height	1.57inches (40MM, 4.0CM)
Shipping Width	4.53inches (115MM, 11.5CM)
Shipping Depth	14.96inches (380MM, 38.0CM)

Color	Black, Grey
Master Carton Dimensions (Length x Width x Height)	16 x 6 x 10inches (400 x 143 x 264MM)
Master Carton Units	6.0
Master Carton Weight	9.48lbs. (4.3)
Units per Pallet	360.0
SCC Codes	1073130432895 4
Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (no %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (no %
Storage Elevation	0-50000ft (0-15000meters)
Conformance	
Approvals	MET Canada, MET USA, UL 1363, UL 1449
Equipment protection policy	Lifetime : \$50000
Standard warranty	Lifetime
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Proposition 65 Warning	Available in Documentation tab