



PH8U2W

RoHS

★★★★★ 5.0 (2) [Write a review](#)

- Outlet Count: 6 8 12
- Color: Black White
- USB Charging: No Yes

Professional-grade Electrical Surge Protection for Computers and Electronics

Includes: User Manual

Technical Specifications

Output

Number of Outlets	8.0
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	6ft (1.83meters)
Number of Power Cords	1
Maximum Input Current	15.0A
Maximum Line Current	15A

Surge Protection and Filtering

Surge energy rating	2160Joules
ts_nm_surge_response	1ns
Peak Current Common Mode	56kAmps
Peak Current Normal Mode	28kAmps

Physical

Maximum Height	1.18inches (30MM, 3.0CM)
Maximum Width	3.05inches (77MM, 7.7CM)
Maximum Depth	11.69inches (297MM, 29.7CM)
Net Weight	1.48lbs. (0.67KG)
Shipping weight	1.71lbs. (0.78KG)
Shipping Height	1.89inches (48MM, 4.8CM)
Shipping Width	5.71inches (145MM, 14.5CM)

Shipping Depth	13.19inches (335MM, 33.5CM)
Color	White
Master Carton Dimensions (Length x Width x Height)	13.78 x 6.3 x 12.6inches (350 x 160 x 320MM)
Master Carton Units	6.0
Master Carton Weight	11.1lbs. (5.03)
Units per Pallet	324.0
SCC Codes	1073130433620 1

Environmental

Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (no %)
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (no %)
Storage Elevation	0-50000ft (0-15000meters)

Conformance

Approvals	FCC Part 15 Class B, MET Canada, MET USA, UL 1363, UL 1449, UL 60950-1
Equipment protection policy	Lifetime : \$150000
Standard warranty	Lifetime

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Proposition 65 Warning	Available in Documentation tab