



RBC43

★★★★★ 4.9 (7) [Write a review](#)



Genuine APC RBC(TM) are tested and certified for compatibility to restore UPS performance to the original specifications.

Includes: All required connectors, Battery recycling guide, Installation Guide, Metallic battery tray or enclosure, Reusable packaging

Technical Specifications

Input

Number of Power Cords	1
-----------------------	---

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	Enclosed battery cartridge
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Volt-Amp-Hour Capacity	480

Physical

Maximum Height	3.0inches (76MM, 7.6CM)
Maximum Width	8.5inches (216MM, 21.6CM)
Maximum Depth	21.0inches (533MM, 53.3CM)
Net Weight	42.0lbs. (19.09KG)
Shipping weight	45.0lbs. (20.45KG)
Shipping Height	9.0inches (229MM, 22.9CM)
Shipping Width	15.5inches (394MM, 39.4CM)
Shipping Depth	30.25inches (768MM, 76.8CM)
Units per Pallet	12.0

Environmental

Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000ft (0-15000meters)

Conformance

Standard warranty	1 year repair or replace, 30 days (Japan only)
--------------------------	--

Sustainable Offer Status

RoHS	Compliant
-------------	-----------

REACH	REACH: Contains No SVHCs
--------------	--------------------------

PEP	Available in Documentation tab
------------	--------------------------------

EOLI	Available in Documentation tab
-------------	--------------------------------

Proposition 65 Warning	Available in Documentation tab
-------------------------------	--------------------------------
