



SMT3000RM2UNC

★★★★★ 5.0 (1) [Write a review](#)

Power 750VA 1000VA 1500VA 2200VA 3000VA

Network Card No Yes

Smart Connect No Yes



Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other..

Includes: CD with software, Documentation CD, Installation guide, Rack mounting hardware, Rack Mounting support rails, Smart UPS signalling RS-232 cable, USB cable

Technical Specifications

Output

| | |
|----------------------------------|--|
| Output power capacity | 2.7kWatts / 2.88kVA |
| Max Configurable Power (Watts) | 2.7kWatts / 2.88kVA |
| Nominal Output Voltage | 120V |
| Output Voltage Distortion | Less than 5% |
| Output Frequency (sync to mains) | 50/60Hz +/- 3 Hz |
| Topology | Line Interactive |
| Waveform type | Sine wave |
| Output Connections | (2) NEMA 5-20R (Battery Backup) (6) NEMA 5-15R (Battery Backup) |
| Transfer Time | 4ms typical : 8ms maximum |

Input

| | |
|--|----------------------------------|
| Nominal Input Voltage | 120V |
| Input frequency | 50/60 Hz +/- 3 Hz (auto sensing) |
| Input Connections | NEMA L5-30P |
| Cord Length | 8ft (2.44meters) |
| Input voltage range for main operations | 82 - 144V |
| Input voltage adjustable range for mains operation | 75 - 154V |
| Number of Power Cords | 1 |

Batteries & Runtime

| | |
|-----------------------|--|
| Battery type | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof |
| Typical recharge time | 3hour(s) |
| Replacement Battery | RBC43 ↗ |

| | |
|---------------------------------------|--|
| Expected Battery Life (years) | 3 - 5 |
| RBC Quantity | 1 |
| Battery Volt-Amp-Hour Capacity | 566 |
| Runtime | View Runtime Graph View Runtime Chart |
| Efficiency | View Efficiency Graph |

Communications & Management

| | |
|---------------------------------------|---|
| Interface Port(s) | RJ-45 Serial, SmartSlot, USB |
| Pre-Installed SmartSlot™ Cards | AP9631 ↗ |
| Control panel | LED status display with On Line : On Battery : Replace Battery and Overload indicators, Multi-function LCD status and control console |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

Surge Protection and Filtering

| | |
|----------------------------|-----------|
| Surge energy rating | 459Joules |
|----------------------------|-----------|

Physical

| | |
|------------------------|-----------------------------|
| Maximum Height | 3.39inches (86MM, 8.6CM) |
| Maximum Width | 18.9inches (480MM, 48.0CM) |
| Maximum Depth | 26.89inches (683MM, 68.3CM) |
| Rack Height | 2U |
| Net Weight | 97.62lbs. (44.28KG) |
| Shipping weight | 113.94lbs. (51.68KG) |
| Shipping Height | 10.0inches (254MM, 25.4CM) |
| Shipping Width | 23.62inches (600MM, 60.0CM) |
| Shipping Depth | 38.6inches (980MM, 98.0CM) |
| Color | Black |

Environmental

| | |
|--|---------------------------|
| Operating Temperature | 32 - 104 °F (0 - 40 °C) |
| Operating Relative Humidity | 0 - 95 % |
| Operating Elevation | 0-10000ft (0-3000meters) |
| Storage Temperature | -15 - 45 °C |
| Storage Relative Humidity | 0 - 95 % |
| Storage Elevation | 0-50000ft (0-15000meters) |
| Audible noise at 1 meter from surface of unit | 55.0dBA |
| Online thermal dissipation | 348.0BTU/hr |

Conformance

| | |
|------------------------------------|-----------------------------------|
| Approvals | CSA, FCC Part 15 Class A, UL 1778 |
| Equipment protection policy | Lifetime : \$150000 |

| | |
|--------------------------|---|
| Standard warranty | 3 years repair or replace (excluding battery) and 2 years for battery |
|--------------------------|---|

Sustainable Offer Status

| | |
|-------------|-----------|
| RoHS | Compliant |
|-------------|-----------|

| | |
|--------------|--------------------------|
| REACH | REACH: Contains No SVHCs |
|--------------|--------------------------|

| | |
|--------------------------|-----------|
| Battery Directive | Compliant |
|--------------------------|-----------|

| | |
|-------------------------------|--------------------------------|
| Proposition 65 Warning | Available in Documentation tab |
|-------------------------------|--------------------------------|