

Wireless Essentials® Accessory Microphones and Input Cables

For all Audio-Technica UniPak® Wireless Systems



WIRELESS LAVALIER MICROPHONES

Operation: These microphones' small size allows them to be worn as a lavalier, or hidden in loose clothing. For normal lavalier use, attach the microphone about 6" (15 cm) below the user's chin. Anticipate movements that may cause the microphone to rub against or be covered by clothing and position the microphone to avoid it.

AT829cW Cardioid Condenser Wireless Lavalier Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessories Furnished:	Clothing clip; windscreen

AT831cW Cardioid Condenser Wireless Lavalier Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessories Furnished:	Clothing clip; windscreen

MT830cW Omni Condenser Wireless Lavalier Microphone

Element:	Condenser
Polar Pattern:	Omnidirectional
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessories Furnished:	Clothing clip; press-on windscreens

MT830cW-TH Omni Condenser Wireless Lavalier Microphone

Element:	Condenser
Polar Pattern:	Omnidirectional
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessories Furnished:	Clothing clip; press-on windscreens



WIRELESS BOUNDARY MICROPHONE

Operation: The microphone should be placed on a flat, unobstructed mounting surface, with the front of the microphone facing the sound source. The sound source should not be below, or higher than 60° above, the plane of the mounting surface.

U851cW Cardioid Condenser Wireless Boundary Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	29.5" (0.75 m) cable terminated for use with Audio-Technica UniPak® body-pack transmitters



WIRELESS GOOSENECK MICROPHONE

Operation: The microphone direct mounts to any 5/8"-27 stand, or to the included threaded mounting flange. Cable exit is from the bottom of the microphone. If necessary, the included pass-through adapter may be used to provide a side exit for the cable.

U857ALcW Cardioid Condenser Wireless Gooseneck Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	29.5" (0.75 m) cable terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessories Furnished:	AT8153 two-stage foam windscreen; AT8663 A-mount flange; AT8664 A-mount cable pass-through adapter



WIRELESS CLIP-ON INSTRUMENT MICROPHONES

Operation: Clip directly on to instrument. The microphone is uniquely capable of picking up high-intensity sound without distortion.

ATM350cW Cardioid Condenser Wireless Instrument Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessories Furnished:	AT8418 UniMount® instrument mount; AT8468 violin mount

PRO 35cW Cardioid Condenser Wireless Instrument Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessory Furnished:	AT8418 UniMount® instrument mount



WIRELESS HEADWORN MICROPHONES

Operation: After use in high-moisture applications, such as aerobics instruction, on-stage performing, etc., remove the foam screen, wipe off the headset with a towel and permit them to air-dry. (Do not store in a closed space, such as a plastic bag, until all moisture has evaporated.)

ATM73cW: Wear the headband around the back of the head with each cushioned support pad resting on the temple in front of the ear.

ATM75cW and PRO 8HEcW: Wear the headband around the back of the head with each cushioned support pad resting on the temple in front of the ear. The assembly may be oriented so that the microphone descends from either the left or right side. The cable should remain clipped to the headband, with some slack at the boom connection.

AT889cW: Position the adjustable band around the back of the neck, placing the cushioned earpieces over each ear. Adjust the headband as necessary for a stable, comfortable fit.

ATM73cW Cardioid Condenser Wireless Headworn Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessories Furnished:	Windscreens

ATM75cW Cardioid Condenser Wireless Headworn Microphone

Element:	Condenser
Polar Pattern:	Cardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessory Furnished:	Windscreen

PRO 8HEcW Hypercardioid Dynamic Wireless Headworn Microphone

Element:	Dynamic
Polar Pattern:	Hypercardioid
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessory Furnished:	Windscreen


AT889cW Noise-cancelling Condenser Wireless Headworn Microphone

Element:	Condenser
Polar Pattern:	Noise-cancelling
Cable:	55" (1.4 m), terminated for use with Audio-Technica UniPak® body-pack transmitters
Accessories Furnished:	Windscreen; clothing clip



Wireless Essentials® Accessory Microphones and Input Cables

Audio-Technica U.S., Inc. 1221 Commerce Drive, Stow, Ohio 44224
P52041 © 2008 Audio-Technica U.S., Inc. Printed in U.S.A.



GUITAR AND MICROPHONE

CABLES

Operation:

AT-GcW, AT-GcW PRO, AT-GRcW, AT-GRcW PRO: Connects electric guitar, bass and other instruments with a ¼" output jack to an Audio-Technica UniPak® body-pack transmitter.

XLRW: Connects a Lo-Z microphone with an XLRM-type output to an Audio-Technica UniPak® body-pack transmitter.

AT-GcW Hi-Z Instrument/Guitar Input Cable (¼" straight connector)

Length:	36" (0.9 m)
Connectors:	¼" phone plug to HRS connector for use between instrument and Audio-Technica UniPak® transmitters

AT-GcW PRO Professional Hi-Z Instrument/Guitar Input Cable (¼" straight connector)

Length:	0.9 m (36")
Connectors:	Switchcraft® ¼" straight connector to HRS-type (locking 4-pin) connector for use between instrument and Audio-Technica UniPak® body-pack wireless transmitters

AT-GRcW Hi-Z Instrument/Guitar Input Cable (¼" right-angle connector)

Length:	0.9 m (36")
Connectors:	¼" right-angle overmolded connector to HRS-type (locking 4-pin) connector for use between instrument and Audio-Technica UniPak® body-pack wireless transmitters

AT-GRcW PRO Professional Hi-Z Instrument/Guitar Input Cable (¼" right-angle connector)

Length:	0.9 m (36")
Connectors:	Switchcraft® ¼" right-angle connector to HRS-type (locking 4-pin) connector for use between instrument and Audio-Technica UniPak® body-pack wireless transmitters

XLRW Microphone Input Cable

Length:	29.5" (0.75 m)
Connectors:	XLRF-type connector to HRS connector for use between Lo-Z microphone and Audio-Technica UniPak® body-pack transmitters

¹ Specifications are subject to change without notice.