

## HDMI / VGA Wall Plate to HDBaseT Extender

### Features

- ◆ 1 HDMI Input with Audio for DVI
- ◆ 1 VGA with Audio Converted to HDMI
- ◆ VGA can Accept YPbPr, S-Video, & Video
- ◆ 1 LAN Connector (DXW-2E, DXW-2EU)
- ◆ HDBaseT 600ft (183m) Extension\*
- ◆ 2 USB 2.0 Ports (DXW-2EU)
- ◆ USB Extends Independently 220ft
- ◆ 1 IR Receiver (40ft Range)
- ◆ Auto Sense, Buttons, RS-232 for Source Select
- ◆ Buttons Backlight (Red, Green, Blue)
- ◆ Available in White or Black
- ◆ HDCP Compliant
- ◆ Remote or Local Power
- ◆ Fits in Standard 2 Gang Outlet Box
- ◆ Low Depth for Floor & Table Boxes



**DXW-2EU-W**

**Patents Pending  
Made in the USA**



**DXW-2E-W**



**DXW-2-W**

The DXW-2 Series available in white or black are 2 gang multi-input Decora® style wall plates with HDBaseT CAT extension. Its ability to convert VGA (YPbPr, S-Video, Video) with audio to HDMI locally and transmit the signal up to 600ft\* sets this unit apart from the competition. The sources are remotely selectable via RS-232 commands sent through the matching receiver device (DXE-CAT-RX, DXM Matrixes, etc). In addition, there is a LAN port (DXW-2E, DXW-2EU) for connection to the network without requiring a separate wall plate. THE DXW-2EU has two USB ports for powering USB devices and transmitting 480Mbps up to 220ft independently to a different location. The DXW-2 Series can be remotely powered by the receiver device and also has the ability to transmit IR signals via the sensor window on the front of the unit for remote control of IR controllable devices. Overall, the DXW-2 saves money and simplifies an installation by combining the functionality of a switcher, converter, and extender into one neat package.

*Note: Specifications subject to change without notice.*

*\*Refer to User Guide for full specification*