

BarnMini-12 - SFP+ to SFP+ Converter 12G



BarnMini-12 supports data rates up to 12Gbit/s. It can handle 12G, 10G, 6G and any other video format with a lower data rate than 12Gbit/s. It is equipped with a re-clocker. As any BarnMini module it is available as a standalone unit with a separate PSU or mounted into the BarnMini BTF-Mini-16 frame that houses any combination of 16 x BarnMini modules with a common PSU.



Technical Specifications

SFP/SFP+ ports
<ul style="list-style-type: none">• 2x Port for Small Form-Factor Pluggable Plus (SFP+) and SFP, supports MSA-compliant (multi source agreement) transceivers• Suitable for optical transceivers (singlemode/multimode), SFP/SFP+ media converters (HDMI, Ethernet, SDI, CVBS etc.)• SMPTE 259M, 292M, 372M, 424M, 372M, ST-2081, ST-2082, DVB-ASI, AES10 (MADI), AES3, Ethernet, proprietary protocols• Hot pluggable/swappable
Power Supply
<ul style="list-style-type: none">• 12-24V DC power supply included• redundant power supply available with BTF-Mini-16
Physical Size
<ul style="list-style-type: none">• 92mm x 98mm x 22mm• 200g
Model Name
<ul style="list-style-type: none">• BM-12

