



**Part Number: 4794R**

12 GHz Coax, 4K UHD Precision Video Cable, RG-7 Series, 75 Ohm, 16 AWG Solid, CMR

## Product Description

12 GHz, 4K UHD Precision Video Cable, RG-7 Series, 75 Ohm 16 AWG solid 0.051" silver-plated copper conductor, gas-injected foamed high-density polyethylene insulation, Duofoil® bonded to the core + tinned copper braid shield (95% coverage) plus Beldfoil® with shorting fold, PVC jacket

## Technical Specifications

### Product Overview

Environmental Space:	Outdoor - Aerial
Suitable Applications:	SMPTE 2082-1 12 Gb/s UHDTV, SMPTE 2081-1 6 Gb/s UHDTV, SMPTE 424M 3 Gb/s HD-SDI 1080p

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
16	Solid	SPC - Silver Plated Copper	0.051 in	1

Conductor Count:	1
AWG Size:	16

#### Outer Shield Material

Type	Description	Layer	Material	Material Trade Name	Coverage [%]
Tape		1	Aluminum Foil-Polyester Tape-Aluminum Foil	Bonded Duofoil® (Bonded to Dielectric)	100 %
Braid		2	TC - Tinned Copper		95 %
Tape	Bonded to jacket	3	Polyester Tape-Aluminum Foil	Bonded Beldfoil® with shorting fold (bonded to jacket)	100 %

#### Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.320 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
4.0 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield
15.5 pF/ft

#### Impedance

Nominal Characteristic Impedance
75 Ohm

#### Return Loss (RL)

Frequency [MHz]	Minimum Return (RL)
5 MHz - 1600 MHz	23 dB
1600 MHz - 4500 MHz	21 dB
4500 MHz - 12000 MHz	15 dB

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
-----------------	---------------------

1 MHz	0.26 dB/100ft
3.58 MHz	0.43 dB/100ft
5 MHz	0.50 dB/100ft
6 MHz	0.52 dB/100ft
7 MHz	0.55 dB/100ft
10 MHz	0.63 dB/100ft
12 MHz	0.66 dB/100ft
25 MHz	0.88 dB/100ft
55 MHz	1.21 dB/100ft
67.5 MHz	1.31 dB/100ft
71.5 MHz	1.34 dB/100ft
88.5 MHz	1.47 dB/100ft
100 MHz	1.54 dB/100ft
135 MHz	1.75 dB/100ft
143 MHz	1.79 dB/100ft
180 MHz	1.98 dB/100ft
270 MHz	2.40 dB/100ft
360 MHz	2.76 dB/100ft
540 MHz	3.41 dB/100ft
720 MHz	3.96 dB/100ft
750 MHz	4.05 dB/100ft
1000 MHz	4.70 dB/100ft
1500 MHz	5.83 dB/100ft
2000 MHz	6.80 dB/100ft
2250 MHz	7.25 dB/100ft
3000 MHz	8.48 dB/100ft
4500 MHz	10.66 dB/100ft
6000 MHz	12.47 dB/100ft
12000 MHz	19.45 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.2 ns/ft	85 %

#### Voltage

UL Voltage Rating
300V RMS

Electrical Characteristics Notes:	Return Loss: Fixed bridge and termination
-----------------------------------	---

#### Temperature Range

Operating Temp Range:	-30°C To +75°C
-----------------------	----------------

#### Mechanical Characteristics

UV Resistance:	Yes
Bulk Cable Weight:	59 lbs/1000ft
Max Recommended Pulling Tension:	111 lbs
Min Bend Radius/Minor Axis:	3.25 in

#### Standards

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca
RG Type:	RG-7/U Type
Series Type:	Series 7

#### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes

EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2000/53/EC (ELV)
EU Directive Compliance:	EU Directive 2002/96/EC (WEEE)
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU Directive Compliance:	EU Directive 2011/65/EU (ROHS II)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	Yes - Black only, when supported by messenger wire
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes - Black only

## Flammability, LSOH, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL1666 Vertical Shaft

## Part Number

Plenum (Y/N):	No
---------------	----

## Variants

Item #	Color	Footnote
4794R 0101000	BLACK	C
4794R 0102500	BLACK	C Z
4794R 0061000	BLUE, LIGHT	
4794R N3U1000	MIL GREEN	
4794R 0031000	ORANGE	
4794R 0071000	PURPLE	
4794R 0021000	RED	
4794R 0041000	YELLOW	

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.