

Part Number: 8421

Audio & Instrumentation, 25 AWG TC, O/A Braid, CM



Product Description

25 AWG Stranded (7x33) Tinned Copper/Tinned Copper Covered Steel conductor, FPE insulation, tinned copper spiral wrapped shield (85% coverage), PVC jacket.

Technical Specifications

Product Overview

Environmental Space:	Indoor (Not Riser or Plenum)
Suitable Applications:	Audio Connecting Cable

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Coax
25	7x33	TC/TCCS -Tinned Copper/Tinned Copper Covered Steel	1
Conductor Count:		1	
AWG Size:		25	

Insulation

Material	Nominal Diameter
FPE - Foamed Polyethylene	0.125 in

Outer Shield Material

Type	Material	Coverage [%]
Spiral Serve	TC - Tinned Copper	85 %

Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.18 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
32.27 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield
16 pF/ft

Impedance

Nominal Characteristic Impedance
80 Ohm

Current

Max. Recommended Current [A]
1.9 Amps per conductor @ 25°C

Voltage

Non-UL Voltage Rating
300V RMS

Temperature Range

Non-UL Temp Rating:	80°C
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	15 lbs/1000ft
Max Recommended Pulling Tension:	5 lbs
Min Bend Radius (Overall):	2 in

Standards

CPR Euroclass:	Fca
----------------	-----

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Part Number

Plenum (Y/N):	No
---------------	----

Variants

Item #	Color
8421 060250	BLACK

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.