

For more Information
please call

1-800-Belden1



General Description:

Stranded tinned copper conductor (Uni-Strand®).

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	18	7x26	Uni-Strand® (TC- Tinned Copper)

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.0315

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.108 in.

Mechanical Characteristics (Overall)

UL Temperature Rating: 105°C (UL AWM Style 1015)

Bulk Cable Weight: 9.800 lbs/1000 ft.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL AWM Style: UL Style 1015 (600 V 105°C)

UL Rating: 600 V, 105°C

CSA Rating: 600 V, 105°C

CSA Type: TEW

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

Flame Test

UL Flame Test: VW-1

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Max. Operating Voltage - UL:

Voltage

600 V RMS (UL AWM Style 1015)

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
32718 0024000	4,000 FT	40.000 LB	RED	C	#18 STR PVC RED
32718 0034000	4,000 FT	44.000 LB	ORANGE		#18 STR PVC ORG

Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

32718 Hook-up/Lead - UL AWM Style 1015

32718 0044000	4,000 FT	44.000 LB	YELLOW		#18 STR PVC YEL
32718 0094000	4,000 FT	44.000 LB	WHITE	C	#18 STR PVC WHT
32718 0104000	4,000 FT	44.000 LB	BLACK		#18 STR PVC BLK
32718 0134000	4,000 FT	44.000 LB	BLUE, DARK		#18 STR PVC DBLU

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 06-30-2008

© 2015 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.