

Micro Converter HDMI to SDI



Take the HDMI output from laptop computers or consumer cameras and convert it to SDI for use with broadcast switchers, routers, monitors and more! The multi rate 3G-SDI automatically switches between all SD and HD formats up to 1080p60. You get 2 SDI outputs, support for Level A and Level B equipment, and power over USB!

\$39

Connections

SDI Video Outputs

Automatically matches the SD, HD or 3G-SDI HDMI video input.

HDMI Video Inputs

HDMI Type A in.

Updates, Configurations and Power


Micro USB.

Multi Rate Support

Auto detection of SD or HD.

Reclocking

Yes



Standards

SDI Video Standards

525i59.94 NTSC, 625i50 PAL

SDI Compliance

SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 424M, SMPTE 425M

SDI Color Precision

4:2:2

HD Video Standards

720p50, 720p59.94, 720p60

SDI Video Rates

SDI video connections are switchable between standard definition and high definition, and user selectable level A and B via setup utility.

SDI Color Space

YUV

1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60

1080i50, 1080i59.94, 1080i60

SDI Auto Switching

Automatically detects SD, HD and 3G-SDI

HDMI Video Standards

525i29.97 NTSC, 625i25 PAL
720p50, 720p59.94, 720p60
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60
1080i50, 1080i59.94, 1080i60

HDMI Color Precision

4:2:2

HDMI Color Space

YUV

Copy Protection

HDMI input is unable to capture from copy protected HDMI sources. Always confirm copyright ownership before capture or distribution of content.

Software

Software Control

Mac OSX™ and Windows™ software via micro USB.

Internal Software Upgrade

Via micro USB.

Operating Systems



macOS 10.12 Sierra,
macOS High Sierra 10.13 or later.



Windows 8.1 or Windows 10.

Settings Control

Via software utility.

Power Requirements

Power Consumption

2.0 Watts

Operational Voltage Range

4.4 to 5.25V DC

Environmental Specifications

Operating temperature

0° to 40° C (32° to 104° F)


Storage temperature

-20° to 60° C (-4° to 140° F)

Relative Humidity

0% to 90% non-condensing

Physical Specifications



What's Included

Micro Converter HDMI to SDI

Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2018, all rights reserved.
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.
This website uses remarketing services to advertise on third party websites to previous visitors to our site.
You can opt out at any time by changing cookie settings.

Blackmagic Design Authorized Reseller