



Blonder  
Tongue

**HDE-CHV-QAM/IP**

Single Channel HD Encoder

**SOLUTIONS FOR ALL YOUR APPLICATIONS**

The new and improved **HDE-CHV-QAM/IP** accepts one **HD** program from any of the following inputs: 1xComponent, 1xHDMI (unencrypted), 1xVGA, and 1xComposite. The MPEG-2 encoded outputs are available in 1xQAM and 1xIP (100/1000Base-T Ethernet).

The 1xQAM RF output is frequency agile over the entire CATV frequency range of 5-1002 MHz, including sub channels T7-T14, and 2-158, with an output level of +40 dBmV.

Comprehensive remote monitoring and control is accomplished using any standard Web browser via a front-panel 100/1000 Ethernet connection. A rear-panel VGA output port is available for loop-through applications.

**HD MPEG-2 Encoding**  
**DOLBY® Digital Audio Encoding**

**1xComponent/HDMI/VGA/Composite**

(1 Program)



**Features**

- Accepts one program from any of the following inputs:  
1xComponent, 1xHDMI (unencrypted), 1xVGA, and 1xComposite
- Simultaneously delivers 1xQAM and 1xIP outputs
- Provides +40 dBmV QAM RF output level
- Provides full QAM output coverage from 5 to 1002 MHz (sub channels T7-T14, and 2-158)
- Supports custom video and transport stream bit rate settings
- Supports user-defined PSIP configuration
- Supports Real-time Dolby® Digital audio encoding
- Supports Closed Captioning EIA-608
- Provides comprehensive GUI-based monitoring and control via standard Web browsers
- Compact design permits installation of up to 3 Encoder modules in 1RU

**Ordering Information**

Model	Stock #	Description
HDE-CHV-QAM/IP	6384B	MPEG-2 HD Encoder; 1xComponent/HDMI/VGA/Composite inputs; 1xQAM + 1xIP outputs
HDE-3MCH	6389	1RU Rack mount chassis; holds 3 modules



**Made in U.S.A.**

Dolby® is a registered trademark of Dolby Laboratories.

Rev: 052417

Blonder Tongue is ISO 9001:2015 Certified

# Specifications

## Input

<b>Component</b>	<b>Connectors:</b> 3x RCA for Video (Y, Pb, Pr) <b>Video Resolution:</b> 480i, 720p, & 1080i <b>Video Aspect Ratio:</b> 4:3 & 16:9 <b>Audio:</b> 2x RCA for Analog Audio (L, R) 1x RCA for Digital Audio (PCM)
<b>HDMI</b>	<b>Connector:</b> 1x HDMI <b>Video Resolution:</b> 480i, 720p, & 1080i <b>HDCP Encryption:</b> Not supported <b>Audio:</b> Embedded PCM & pass-through Dolby® Digital only
<b>VGA</b>	<b>Connectors:</b> 2x Female VGA (Input + Loop-through Output) <b>Video Resolution:</b> 640x480 @ 60 fps 800x600 @ 60 fps 1024x768 @ 60 fps <b>Audio:</b> 2x RCA for Analog Audio (L, R) 1x RCA for Digital Audio (PCM)
<b>Composite</b>	<b>Connectors:</b> 1x RCA for Video (Y) <b>Video Resolution:</b> 480i <b>Audio:</b> 2x RCA for Analog Audio (L, R) 1x RCA for Digital Audio (PCM)

<b>Encoding Profile</b>	
<b>Video</b>	<b>Output Format:</b> MPEG-2 HD MP@ML; ISO 13818-2 <b>Chroma:</b> 4:2:0 <b>Resolution:</b> 480i, 720p, & 1080i <b>Frame Rate:</b> 29.97 fps (480i); 29.97 fps (1080i); 59.97 fps (720p) <b>Aspect Ratio:</b> 4:3 & 16:9 <b>GOP Structure:</b> I & P frames (user-selectable) <b>Video Bit Rate:</b> Variable (user-selectable) <b>Video Pre-filter:</b> Variable (user-selectable) <b>Color Space:</b> YCbCr and RGB
<b>Audio</b>	<b>Output Format:</b> Dolby® Digital <b>Sampling Rate:</b> 48 kHz <b>Bit Rate:</b> Variable; 96 - 448 Kbps (user-selectable)
<b>Closed Captioning</b>	<b>Component:</b> EIA-608; 1x RCA (CC) <b>HDMI:</b> EIA-608; 1x RCA (CC) <b>VGA:</b> EIA-608; 1x RCA (CC) <b>Composite:</b> EIA-608

## Alarms/Monitoring/Control

<b>Local Monitoring:</b>	1x Power LED 1x Status LED
<b>Local Control:</b>	1x IP Reset button
<b>Remote Monitoring and Control:</b>	GUI-based menu via standard Web browser (1x RJ45 front-panel connector; 100/1000Base-T, also used for IP output)

## Related Products

Model	Description
HDE-CSV-QAM/IP	MPEG-2 HD Encoder; 1xComponent/HD-SDI/HDMI/VGA/Composite to 1xQAM + 1xASI + 1xIP
HDE-1C-QAM	MPEG-2 HD Encoder; 1xComponent/Composite inputs to 1xQAM + 1xIP
HDE-8C-QAM	MPEG-2 HD Encoder; 8xComponent/Composite + 1xSpare to 4xQAM + 1xASI; EAS
HDE-8C-QAM/IP	MPEG-2 HD Encoder; 8xComponent/Composite + 1xSpare to 4xQAM + 1xASI + 8xIP; EAS

## Output

<b>QAM</b>	<b>Connector:</b> 1x "F" Female (Rear-panel) <b>Modulation:</b> QAM 16, 32, 64, 128, and 256 <b>Standards:</b> ITU-T J.83; Annex A and B <b>DVB Symbol Rate:</b> Variable; up to 7 MSymbol/sec (MBaud) <b>Frequency Range:</b> 5 to 1002 MHz <b>Tuning:</b> CATV Channel Selectable (T7 to T14, 2 to 158) <b>Channels' Bandwidth:</b> 6 MHz <b>RF Level:</b> +40 dBmV ± 1 dB <b>RF Level Adjustment:</b> +35 to +42 dBmV, 1 dB increment <b>Frequency Tolerance:</b> ± 0.5 kHz @ 77 °F (25 °C) <b>Frequency Stability:</b> ± 5 kHz over 32 to 122 °F (0 to 50 °C) <b>Amplitude Flatness:</b> ± 0.25 dB (over 6 MHz channel) <b>Phase Noise:</b> -98 dBc (@ 10 kHz) <b>Spurious:</b> -60 dBc <b>Broadband Noise:</b> -70 dBc (@ +40 dBmV output level, 5.5 MHz bandwidth) <b>Impedance:</b> 75 Ω <b>Spectral Inversion:</b> Auto Recognition <b>Carrier Suppression:</b> 45 dB <b>Return Loss:</b> 14 dB typical <b>Signal-to-Noise Ratio (SNR):</b> 40 dB typical <b>MER:</b> 40 dB typical <b>I/Q Phase Error:</b> Less than 1 degree <b>I/Q Amplitude Imbalance:</b> Less than 1%
<b>IP</b>	<b>Connector:</b> 1x RJ45 (Front-panel) <b>Standard:</b> 100/1000Base-T Ethernet <b>TS Bit Rate:</b> Variable (user-selectable) <b>UDP/RTP:</b> Supported (user-selectable)

## General

<b>Dimensions (W x D x H):</b>	5.65 x 14.10 x 1.72 inches (143.5 x 358.1 x 43.7 mm)
<b>Power:</b>	External Power Supply (Input 120 VAC / output 12 VDC @ 3 Amps)
<b>Power Dissipation:</b>	16 W
<b>Weight (one module):</b>	1.75 lbs (0.795 kg)
<b>Operating Temperature:</b>	32 to 122 °F (0 to 50 °C)
<b>Storage Temperature:</b>	-13 to 158 °F (-25 to 70 °C)
<b>Operating Humidity:</b>	0 to 95% RH @ 35 °C max, non-condensing
<b>Storage Humidity:</b>	0 to 95% RH @ 35 °C max, non-condensing