

PRODUCT NAME	REALiS WUX10 Mark II
ITEM CODE	4231B002
UPC CODE	013803119381



Suggested List Price:

\$12,999.00

FEATURES

- **Native WUXGA Resolution (1920 x 1200)** - Display true wide screen content in high resolution
- **LCOS Technology** - High image quality and reliability
- **AISYS Optical Engine** - Efficiently handles light, producing superior image quality
- **3200 Lumens** - Bright, crisp images
- **Newly Designed 1.5X Zoom Lens** - Genuine Canon Optics
- **Photo Mode** - Make precise adjustments to ensure optimum color accuracy
- **10:0 Lens Offset** - Minimizes the need for keystone correction
- **Advanced Color Management System** - 6-axis color adjustment
- **Deep Color Ver. 1.3 HDMI Input** - Supports full 1080p high definition signal
- **Network Ready RJ-45 Port** - Manage and control multiple projectors from a networked pc
- **Auto Setup** - Automatic input signal and keystone correction
- **Guidance Functions** - On screen help provides easy, step-by-step operation
- **Off and Go** - Internal fan makes it possible to unplug the projector and go
- **Warranty** - 3 Year Parts and Labor / 120 Day on Lamp
- **Canon's Triple P (Projector Protection Program)** - A service program that provides a loaner projector of equal or greater quality to the end user in the event their projector needs to be repaired*

* Based on availability, for complete details contact your Canon sales representative

CONTENTS OF KIT

- REALiS WUX10 Mark II Projector
- Power Cable
- DVI-VGA Computer Cable
- Component Video Cable
- Lens Cap
- Remote Control (with AAA batteries)
- Soft Carrying Case
- Warranty Card

OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION	SUGGESTED LIST PRICE
2396B001	RS-LP04 REPLACEMENT LAMP	579.00
3095B001	RS-CL07 CEILING MOUNT	999.00
3096B001	RS-CL08 CEILING EXTENSION : (16" - 24")*	379.00
3097B001	RS-CL09 CEILING EXTENSION : (24" - 39")*	399.00
7502A001	LV-CA29 DVI-D CABLE	69.00
1332V132	REALiS PROJECTOR CASE	269.00

* Extension for RS-CL07 Ceiling Mount

PACKAGING INFORMATION

PROJECTOR	W x D x H	WEIGHT
REALiS WUX10 Mark II	15.4 x 19.8 x 10.5 in (391 x 503 x 267 mm)	18.38 lbs (8.24 kg)

SPECIFICATIONS

BASIC	IMAGING DEVICE	0.7" Reflective LCD Panels (LCOS x 3)	
	ASPECT RATIO	16:10	
	NATIVE RESOLUTION	WUXGA (1920 x 1200)	
	BRIGHTNESS	3200 Lumens	
	UNIFORMITY	88%	
	CONTRAST	1000:1	
OPTICS	VERTICAL KEYSTONE	+/- 20 degrees (Auto/Manual)	
	PROJECTION LENS	F1.85 - 2.65, f=21.8 - 31.9mm	
	LENS OFFSET	10:0, Fixed	
	ZOOM	1.5x Powered, 12x Digital zoom	
	FOCUS	Powered	
	SCREEN SIZE	40" - 300"	
	PROJECTION DISTANCE COVERAGE	3.9 - 29.9 ft (1.2 - 9.1m) 100°: 9.8 - 16.1 ft. (3.0 - 4.9m)	
	THROW RATIO	1.48 - 2.18:1	
IMAGE ADJUSTMENTS	IMAGE MODE	Standard, Presentation, Movie, sRGB, Photo	
	COLOR ADJUST	Dynamic Gamma, 6-Axis (RGBCMY) Color Adjustment	
	WALL CORRECTION	Auto / Manual	
	IMAGE FLIP	None / Ceiling Mounted / Rear / Rear, Ceiling Mounted	
INPUT SIGNALS	TILT ANGLE	Adjusting foot up to 10 degrees	
	DIGITAL PC INPUT	WUXGA / UXGA / WSXGA+ / SXGA+ / WSXGA / SXGA / WXGA / XGA / SVGA / VGA	
	SCANNING FREQUENCY	H:15-75 kHz, V:50-85 Hz	
	ANALOG PC INPUT	WUXGA / UXGA / WSXGA+ / SXGA+ / WSXGA / SXGA / WXGA / XGA / SVGA / VGA	
	SCANNING FREQUENCY	H:15-75 kHz, V:50-85 Hz	
	DOT CLOCK	170MHz or less	
	VIDEO INPUT	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N	
	COMPONENT INPUT	1080p / 1080i / 1035i / 720p / 576p / 576i / 480p / 480i	
	DIGITAL VIDEO INPUT	HDMI: 1080p / 1080i / 1035i / 720p / 576p / 480p	
	TERMINALS	INPUT	DVI-I 29PIN
HDMI			Version 1.3 Deep Color / Digital Video Input
D-SUB 15PIN			Analog PC Input x 1
RCA			Composite Video Input
OUTPUT		STEREO MINI-JACK	Stereo Audio Input x 3
		D-SUB 15PIN	N/A
CONTROL		STEREO MINI-JACK	Stereo Audio Output x 1
		RS-232	D-sub 9pin
		RJ-45	Yes
BUILT-IN SPEAKER		1W (Mono)	
LAMP	TYPE	275W NSH (AC)	
	LAMP LIFE (NORMAL/QUIET)	2000 / 3000 Hours	
REMOTE CONTROL	SENSOR	Wireless Infrared, Front/Back	
RATINGS	FAN NOISE (NORMAL/QUIET)		35/31 dB
	POWER	CONSUMPTION (NORMAL/QUIET/STANDBY)	400W / 330W / 11W
		VOLTAGE	AC100 to 240V, 50/60Hz
	TEMPERATURE	OPERATING	41° to 95° F (5° to 35° C)
		STORAGE	-22° to 104° F (-30° to 60° C), 5%RH ~ 90%RH
	DIMENSIONS (W x D x H)		11.2 x 13.2 x 4.5 in (284 x 336 x 114 mm)
	WEIGHT		10.9 lbs (4.94 kg)

* All prices, specifications, and availabilities subject to change without prior notice.