

# Cisco MFE and MGE SFP Transceivers

## Cisco Small Business Network Accessories

### Easily Connect Switches with Fiber Optic Networking Modules

#### Highlights

- Adds fiber-optic connectivity to Cisco Small Business and Cisco Small Business Pro Series switches
- High-performance link for connecting networks within a building or small campus area
- Easy removal with an integrated spring latch
- Hot swappable to maintain network availability

#### Product Overview

Cisco® MFE and MGE Small Form-Factor Pluggable (SFP) or mini Gigabit Interface Converter (mini-GBIC) transceivers (Table 1) are easy-to-install modules that provide a simple way to add fiber connectivity or to add an extra Gigabit Ethernet port to your Cisco Small Business or Cisco Small Business Pro Series switches. The transceivers are available for single-mode or multimode fiber-optic cabling and can support distances from 100 meters up to 40 kilometers.

The Cisco MFE and MGE transceivers provide fast and reliable connectivity between switches that are located on different floors, in separate buildings, or on a small campus network needing connectivity between sites. These transceivers can support both Fast and Gigabit Ethernet applications.

**Table 1.** MFE and MGE SFP Transceiver Modules

	Description
<b>MFE Transceivers</b>	
<b>MFEBX1</b>	100BASE-BX-20U SFP transceiver for single-mode fiber, 1310 nm wavelength, support up to 20 km
<b>MFEFX1</b>	100BASE-FX SFP transceiver, for multimode fiber, 1310 nm wavelength, support up to 2 km
<b>MFELX1</b>	100BASE-LX SFP transceiver, for single-mode fiber, 1310 nm wavelength, support up to 15 km
<b>MGE Transceivers</b>	
<b>MGBBX1</b>	1000BASE-BX-20U SFP transceiver, for single-mode fiber, 1310 nm wavelength, support up to 10 km
<b>MGBLH1</b>	1000BASE-LH SFP transceiver, for single-mode fiber, 1310 nm wavelength, support up to 40 km
<b>MGBLX1</b>	1000BASE-LX SFP transceiver, for single-mode fiber, 1310 nm wavelength, support up to 10 km
<b>MGBSX1</b>	1000BASE-SX SFP transceiver, for multimode fiber, 850 nm wavelength, support up to 500 m
<b>MGBT1</b>	1000BASE-T SFP transceiver for category 5 copper wire, support up to 100 m

#### Features

- Built-in spring latch for easy module removal
- Hot swappable
- Low insertion-loss duplex LC receptacle
- Low electromagnetic interference (FCC Part 15, Class B) for clear communications
- Meets FDA and International Electrotechnical Commission (IEC) eye safety standards

## Cisco Limited Warranty

The Cisco Small Business transceivers come with a 5-year limited hardware warranty with return to factory replacement. In addition, Cisco offers software updates for bug fixes at no charge for the life of the warranty and one year of telephone technical assistance from the Small Business Support Center. For more information visit, [http://www.cisco.com/en/US/docs/general/warranty/5year\\_SmallBusiness.html](http://www.cisco.com/en/US/docs/general/warranty/5year_SmallBusiness.html).

## Specifications

Table 2 contains the specifications, package contents, and minimum requirements for the Cisco MFE and MGE SFP Transceivers.

**Table 2.** Specifications for the Cisco MFE and MGE SFP Transceivers

Specifications	
<b>Media</b>	MFEBX1: Single-mode fiber (SMF) MFELX1: Single-mode fiber (SMF) MFEFX1: Multimode fiber (MMF) MGBBX1: Single-mode fiber (SMF) MGBLH1: Single-mode fiber (SMF) MGBLX1: Single-mode fiber (SMF) MGBSX1: Multimode fiber (MMF) MGBT1: Category 5e UTP
<b>Application</b>	MFEBX1: 100BASE-BX-20U MFELX1: 100BASE-LX MFEFX1: 100BASE-FX MGBBX1: 1000BASE-BX-20U MGBLH1: 1000BASE-LH MGBLX1: 1000BASE-LX MGBSX1: 1000BASE-SX MGBT1: 1000BASE-T
<b>Connector type</b>	MFEBX1: Single LC MFELX1: Duplex LC MFEFX1: Duplex LC MGBBX1: Single LC MGBLH1: Duplex LC MGBLX1: Duplex LC MGBSX1: Duplex LC MGBT1: RJ-45
<b>Wavelength typical (Tx)</b>	MFEBX1: 1310 nm MFELX1: 1310 nm MFEFX1: 1310 nm MGBBX1: 1310 nm MGBLH1: 1310 nm MGBLX1: 1310 nm MGBSX1: 850 nm MGBT1: N/A

Specifications	
<b>Wavelength range (Rx)</b>	MFEBX1: 1550 nm MFELX1: 1310 nm MFEFX1: 1310 nm MGBBX1: 1490 nm MGBLH1: 1310 nm MGBLX1: 1310 nm MGBSX1: 850 nm MGBT1: N/A
Performance	
<b>Maximum distance</b>	MFEBX1: up to 20 km MFELX1: up to 15 km MFEFX1: up to 2 km MGBBX1: up to 10 km MGBLH1: up to 40 km MGBLX1: up to 10 km MGBSX1: up to 500 m MGBT1: up to 100 m
<b>Average output power</b>	MFEBX1: -20 dBm to -14 dBm MFELX1: -20 dBm to -14 dBm MFEFX1: -15 dBm to -8dBm MGBBX1: -8 dBm to -3 dBm MGBLH1: -4 dBm to 0 dBm MGBLX1: -9.5 dBm to -3 dBm MGBSX1: -9.5 dBm to -4 dBm MGBT1: N/A
<b>Receiver sensitivity</b>	MFEBX1: -32 dBm (max) MFELX1: -30 dBm (max) MFEFX1: -34 dBm (max) MGBBX1: -23 dBm (typ) MGBLH1: -25 dBm (typ) MGBLX1: -20 dBm (typ) MGBSX1: -20 dBm (typ) MGBT1: N/A
<b>Receiver overload</b>	MFEBX1: -8 dBm (min) MFELX1: -10 dBm (min) MFEFX1: -5 dBm (min) MGBBX1: -3 dBm MGBLH1: -3 dBm MGBLX1: -3 dBm MGBSX1: -0 dBm MGBT1: N/A
Environmental	
<b>Dimensions W x H x D</b>	MFEBX1: 13 x 9 x 56 mm (0.53 x 0.33 x 2.19 in.) MFELX1: 13 x 9 x 56 mm (0.53 x 0.33 x 2.19 in.) MFEFX1: 13 x 9 x 56 mm (0.53 x 0.33 x 2.19 in.) MGBBX1: 13.4 x 8.5 x 55.7 mm (0.53 x 0.33 x 2.19 in.) MGBLH1: 13.4 x 8.5 x 56.5 mm (0.53 x 0.33 x 2.22 in.) MGBLX1: 13.4 x 8.5 x 55.7 mm (0.53 x 0.33 x 2.19 in.) MGBSX1: 13.4 x 8.5 x 56.5 mm (0.53 x 0.33 x 2.22 in.) MGBT1: 13.4 x 8.5 x 66 mm (0.53 x 0.33 x 2.60 in.)
<b>Unit weight</b>	0.018 kg (0.63 oz.)
<b>Power</b>	1W (max)
<b>Operating temperature</b>	32° to 158°F (0° to 70°C)

Specifications	
<b>Storage temperature</b>	-40° to 185°F (-40° to 85°C)
<b>Operating humidity</b>	10% to 85% noncondensing
<b>Storage humidity</b>	5% to 90% noncondensing
Standards	
<b>Compliance</b>	FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B
<b>Safety</b>	FDA 21 CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1, 2
Package Contents	
<ul style="list-style-type: none"> <li>• Cisco SFP transceiver</li> <li>• Quick installation guide</li> </ul>	
Minimum Requirements	
<ul style="list-style-type: none"> <li>• Switch with SFP port. Consult the module's <a href="#">Quick Start Guide</a> for interoperability guidelines.</li> </ul>	

## Ordering Information

Table 3 provides ordering information for the Cisco MFE and MGE Transceivers

**Table 3.** Ordering

MFE and MGE Transceivers	
Product Number	Description
<b>MFEBX1</b>	100BASE-BX-20U SFP transceiver
<b>MFEFX1</b>	100BASE-FX SFP transceiver
<b>MFELX1</b>	100BASE-LX SFP transceiver
<b>MGBBX1</b>	1000BASE-BX-20U SFP transceiver
<b>MGBLH1</b>	1000BASE-LH SFP transceiver
<b>MGBLX1</b>	1000BASE-LX SFP transceiver
<b>MGBSX1</b>	1000BASE-SX SFP transceiver
<b>MGBT1</b>	1000BASE-T SFP transceiver

## Cisco Capital

### Financing to Help You Achieve Your Objectives

Cisco Capital can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more.](#)




---

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)