SSF™ Fiber Optic Fan Out Kits

Part: SSFTM 4, 6, and 12 Strand Fan Out Kits



Cleerline SSF[™] Fanout kits enable fast and easy build up of $250\mu m$ fibers found in today's common micro distribution style cables. The $900\mu m$ color coded buffer tubes allow for the cable's overall jacket to be removed and for each $250\mu m$ fiber to simply be threaded through the corresponding colored tube. To complete, the assembly snaps together requring no additional tooling or epoxy.

Loose tube fanout kits are available in 4, 6, and 12 strand configurations in two different lengths matching to installation requirements. Works with all $250\mu m$ type cabling and industry standard connectors.



FEATURES

- -4, 6, and 12 strand configurations
- -Two different lengths available for each type
- -Tubing colors per TIA/EIA-569-B standard
- -Provides protection to to any installation
- -Easy to assemble, simple snap housing

PART NUMBERS

PART NUMBER	PART DESCRIPTION	LENGTH
FAN0425M250	4 STRAND	25in / 63.5cm
FAN0436M250	4 STRAND	36in / 91.4cm
FAN0625M250	6 STRAND	25in / 63.5cm
FAN0636M250	6 STRAND	36in / 91.4cm
FAN1225M250	12 STRAND	25in / 63.5cm
FAN1236M250	12 STRAND	36in / 91.4cm

SPECIFICATIONS

- -TIA/EIA-568-B compliant
- -ABS Plastic
- -Hytrel furcation tubing
- -900μm O.D.

APPLICATIONS

- -Premise/Enterprise Networks
- -Backbone, Horizontal and FTTx applications
- -Data Center, Enterprise, Broadcast, Industrial
- -Defense, Healthcare and Telco/MSO
- -Field repair/ replacement
- -LAN/WAN connections