



SVR-1100A Waveform Monitor / Vectorscope

1 - Composite (Loop thru Input)

User Select - Overlaid Waveform / Vectorscope

Waveform: Flat, IRE, CHR, 1-H, 2-H, DC Restorer

Vectorscope: Phase Rotation 360°, Subcarrier Capture ± 50Hz

In Stock



SVR-1100B Waveform Monitor / Vectorscope

2 - Composite, 1 - External Reference (Loop thru Inputs)

User Select - Overlaid Waveform / Vectorscope / External Reference

Waveform: Flat, IRE, CHR, 1-H, 2-H, DC Restorer

Vectorscope: Phase Rotation 360°, Subcarrier Capture ± 50Hz

In Stock

General Specifications: Unit Available in NTSC or PAL

	<u>NTSC</u>	<u>PAL</u>
CRT Size:	6" Hi-Res	6" Hi-Res
Composite Video:	1V p-p into 75 Ohms	1V p-p into 75 Ohms
Y/C - Luminance:	1.0V p-p into 75 Ohms	1.0V p-p into 75 Ohms
Y/C - Chroma:	0.286V p-p, at burst level into 75 Ohms	0.286V p-p, at burst level into 75 Ohms
External Reference:	1V p-p into 75 Ohms	1V p-p into 75 Ohms
Color Subcarrier Frequency:	3. 579545 MHz ± 10	4. 43361875 MHz ± 10
Weight:	15 - 22 lbs	15 - 22 lbs
Size:	6.5 (H) x 11.5 (W) x 15.5 (D)	6.5 (H) x 11.5 (W) x 15.5 (D)
AC Power, Universal:	100V - 240V 50 / 60 Hz, 25W	100V - 240V 50 / 60Hz, 25W