

<b>Model Name</b>	<b>HS-1300</b>
<b>Product Name</b>	<b>6-Channel HD Portable Video Streaming Studio</b>
<b>Video Standard</b>	HD
<b>Video Format</b>	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
<b>Input Routable / Crosspoint</b>	All 6, repeatable
<b>Video Input</b>	4x HD-SDI 2x HDMI
<b>Computer Graphic Interface</b>	2 via HDMI
<b>Down-converted output</b>	N/A
<b>Video output</b>	3x HDMI + 2x SDI assignable: AUX 1-6, PGM, PVW, PGM Clean or multiview
<b>Audio input</b>	2x Balanced XLR
<b>Audio output</b>	1x Stereo headphone
<b>Embedded audio support</b>	2 ch Audio embedded
<b>Audio Delay Calibration</b>	N/A
<b>A+V switching</b>	N/A
<b>USK</b>	2x USK support Chromakey
<b>DSK</b>	2x DSK support Lumakey & Linear key (Key / Fill)
<b>Picture in Picture</b>	1
<b>Logo Insertion</b>	N/A
<b>Built-in Audio Mixer</b>	selectable audio follow video master gain control
<b>Built-in Monitor Display</b>	17.3" HD TFT LED backlit, 1600x900 pix
<b>Built-in Intercom &amp; Tally</b>	N/A
<b>Streaming Video Encode</b>	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
<b>Streaming Audio Encode</b>	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit

<b>Streaming Protocol</b>	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP (Publish)
<b>Streaming Control</b>	Web browser UI for configuration and control Socket commands
<b>Recording file system</b>	FAT, exFAT, NTFS
<b>Recording file format</b>	MP4
<b>Recording Setting Control</b>	Web UI for system configuration and control
<b>Dimension (LxWxH)</b>	455 x 355 x 134 mm
<b>Weight</b>	16.3 Lbs (7.4 Kg), Reinforce Plastic Case
<b>Accessory</b>	CB-22H/23H/46/47/60/61/62