

# Bridge X\_SH

SDI TO HDMI



#### Bridge X\_SH



#### Descriptions

Bridge X\_SH is a device that convert to HDMI signal from an SDI signal of SMPTE standards. The format is supported from 480i to 1080p60.

In addition, it can insert analog audio into HDMI signal and extract analog audio from HDMI signal.

#### Feature

- SDI to HDMI converter
- Zero delay conversion & timing
- 1 SDI input (SD/HD/FHD all standard format)
- 1 HDMI output (SD/HD/FHD all standard format)
- 1 External stereo analog audio input / output (MUX or DMX)
- Selectable mux audio source between embedded HDMI and analog
- USB power are also available
- DC 7V ~ 17V wide operating power range
- Support rack mount frame (1U max 6 units)

#### Physical

Dimension (W x H x D)	70 x 90 x 22 (mm)
Weight	120g
Power Level	7V ~ 17 VDC
Power Consumption	4 Watts (Max: 4.5Watts)
Operating Temperature	-20℃ ~ 70℃
Humidity	0 to 95% RH, non-condensing
Data Rate	3G
Signal Level	800mVp-p +/- 50m

### Image View





# Drawing Dimension [mm]



# Digital Video Specs.

- Supports HDMI v1.3
- Supports multi-rate SDI formats
- SMPTE 125M: NTSC (480i 59.94), PAL (576i 50)
- SMPTE 296M: 720p (60/59.94/50)
- SMPTE-274M,SMPTE-292M: 1080i (60/59.94/50), 1080p (30/29.97/25/24/23.98)
- SMPTE-424M: 1080p (60/59.94) 3G

#### DIP S/W Function



# Format Support

