

PEARL-2

# Simplify your 4K live video production





## Epiphan Pearl-2™ All-in-one live video production

Reliable, simple live streaming with Pearl-2's integrated live video production workflow. Manage your streaming, recording, and live switching in one place with this easy-to-use video production system.





## Stunning 4K video

Harness the power of Pearl-2's 6<sup>th</sup> generation Intel processor to capture stunning 4K video at 30 fps. Use Pearl's default hardware-accelerated H.264 encoding for maximum compatibility and performance, or choose MPEG-4 or M-JPEG codecs.




## Pro audio support

Capture embedded HDMI, SDI, and USB audio or use the XLR/RCA ports for professional level audio from mixing consoles and sound equipment. Built-in attenuation and gain adjustment mean you get perfect sound fidelity.

## Epiphan Live

Simple-to-use monitoring and live switching between sources or layouts using Epiphan Live, a control interface designed for touch screen devices.



## Plug and play, or tweak to perfection


Let Pearl-2 set everything for you automatically, or use the web-based Admin panel to configure bitrate, frame size, layouts, and more!

## Output video for local displays

Show any source or program channel at front of house or on a larger confidence monitor at up to 4K using Pearl-2's HDMI output ports.



LOCAL DISPLAYS



## Keep your recordings safe

Hold hundreds of hours of HD recordings on the 512 GB solid state hard-drive and configure automatic file transfer to a local USB drive with USB 3.0 file transfer speed or to network drives.




## Capture 6 video sources at once

Pearl-2 works with any video source from SD to 4K! Capture 4K from HDMI, SDI, and USB sources and up to 1080p from IP cameras over RTSP.

## Stream to viewers everywhere

Send multiple, simultaneous streams out to CDNs or video portals. At the same time, use the built-in streaming server to stream locally to web browsers and set-top boxes.



## Switch video sources live

Use the touch screen or Epiphan Live to preview and change live content. See changes immediately in your video stream on Pearl-2's video output ports.

## Create custom layouts

Completely customizable, drag and drop layouts with cropping, chroma key, custom backgrounds, text, timestamping, and image overlay support.



# Models



## PEARL²

For portable live production. Includes a hard-shell carrying case.

## PEARL² RACKMOUNT

All the same features but designed for installation in a rack.



## PEARL² RACKMOUNT TWIN

Two completely independent Pearl-2 systems for high-density rack installation.



# Connect everything!




## Video inputs

Connect your camera or video source with HDMI, SDI, DVI, and USB video inputs



## Pro audio

Use the XLR, TRS, or RCA inputs for pro level audio



\* Specifications are for Pearl-2 and Pearl-2 Rackmount. Pearl-2 Rackmount Twin is comprised of two independent Pearl-2 systems.

Video inputs	<b>Connectors:</b>	2 × HDMI™, 2 × 4K HDMI, 2 × 12G SDI, 2 × USB video
	<b>Network inputs:</b>	RTSP sources over IP
Audio inputs		2 × XLR (stereo), 2 × SDI, 2 × USB, 4 × HDMI, 1 × RCA (stereo)
Video output		On-board touch screen and 2 × 4K HDMI for video output
Video switching		During live streaming and recording via the touch screen or web UI
Video encoding	<b>Codecs:</b>	H.264, MPEG-4, Motion JPEG
	<b>Bitrate:</b>	1 to 50 Mb/s
	<b>Color resolution:</b>	4:2:0
	<b>Resolution:</b>	User selectable up to 4K (3840 × 2160)
Encoded programs		2 simultaneous 1080p programs at 60 fps (with up to 6 HD sources) 6 simultaneous 1080p programs at 30 fps (with up to 6 HD sources) 1 4K UHD program at 30 fps (with up to two 4K and two HD sources)
Audio encoding		MP3, PCM, and AAC (sampling 16 to 48 kHz, bitrate up to 320 kbps)
Network		1 × 10/100/1000 Ethernet port (RJ45)
Storage	<b>Local hard drive:</b>	512 GB SSD
	<b>Local USB:</b>	Automatic or manual copy via 3 USB 3.0 ports
	<b>Network storage:</b>	FTP, SFTP, SCP, RSYNC, CIFS, AWS, or WebDav servers
Recording formats		AVI, MP4, MOV, or MPEG-TS
Control		Web Admin panel, Epiphan Live portal, touch screen, comprehensive HTTP and RS-232 APIs
Product dimensions		<b>Pearl-2:</b> 11 13⁄16" × 9 7⁄16" × 3 17⁄32" (300 mm × 240 mm × 90 mm), 8.38 lbs (3.8 kg) <b>Pearl-2 Rackmount and Pearl-2 Rackmount Twin:</b> 19 5⁄8" × 10 7⁄8" × 3 1⁄2" (498 mm × 276 mm × 89 mm), 11.9 lbs and 14.7 lbs (5.4 kg and 6.6 kg)

[www.epiphan.com](http://www.epiphan.com)

Email: [info@epiphan.com](mailto:info@epiphan.com)  
North America +1-877-599-6581  
International +1-613-599-6581

™ and © 2018 Epiphan Systems Inc. All rights reserved.

Epiphan, Epiphan Video, Epiphan Systems, its products names and logos are tradenames or trademarks of Epiphan Systems Inc. All other company, interface and product names and logos are trademarks or registered trademarks of their respective owners in certain countries. Product descriptions and specifications regarding the products in this document are subject to change without notice.

BR127-7