

Description

The RMC-2101 provides nine available slots for either the FOI-2xxx or FOI-4xxx fiber optic isolator series.

The tenth available slot must be occupied by a PSM-2010 power supply



module. Each RMC-2101 will be shipped with one PSM-2010. A second PSM-2010 may also be added for power redundancy, leaving eight available slots for any fiber optic isolator. If the first PSM-2010 fails, the second PSM-2010 will take over the entire system load and carry on normally. Each fiber optic isolator must also be accompanied by a CMA-2001 chassis mount adapter, which

slides the fiber optic isolator must also be accompanied by a CMA-2001 chassis mount adapter, which slides the fiber optic isolator into the slots and assures correct alignment of the isolator power connector to the power bus inside the RMC-2101.


FiberPlex recommends an "R" chassis for high security applications because they have added power line filtering to contain their RFI emissions.


Rack Mount Chassis


3-1/2" H x 19" W rear access with front exhaust fans

Features:

- Up to nine fiber optic isolators can be mounted inside.
- Each fiber optic isolator is accessible and removable through the rear of the chassis.
- Power redundancy is available through an optional second power supply module.
- Enhanced air flow through two front exhaust fans.











Fan Specifications

Speed	Max Air Pressure		Air Flow		Noise
2500 RPM	3.5 mmH2O	0.14 InchH2O	50.5 CFM	1.43 m3/min	34dBA @ 1M

Physical Dimensions

Height	Width	Depth	Weight
3.5 in (89mm) 19 in (483 mm)		11.35 in (288 mm)	16 lb (7.25 kg)


Specifications - PSM-2010

		Min	Тур	Max	Unit
Power Supply	Input Voltage	85	-	250	VAC
	Input Frequency	40	-	400	Hz
	Input Power	-	75	-	W
	Output Voltage	-	9	-	VDC
	Supply Current	-	8.3	-	А
	Ouput Power	-	75	-	W
Environmental	Storage Temperature	-40	-	85	℃
	Operating Temperature	0	-	50	℃
		Length	Width	Height	Weight
Case Dimensions	PSM-2010	6.375 in (162 mm)	1.57 in (40 mm)	2.844 in (72 mm)	1.6 lb (0.7 kg)

Accessories

Model	Description	
CMA-2001	Chassis Mount Adapter for FOI-2xxx and FOI-4xxx series	
PSM-2010	Power Supply Module for RMC-2101	

Ordering Information



Standard Options:

RMC-2101 RMC-2101R