

CHRB550-v2

Kit with 5 x IB508-v2 LED Studio Lights

ONE SHEET

Overview

The 5-Point Light Kit features include 3200K-5600K Bi-Color capabilities and a 60-degree angle that delivers reliable, consistent performance.

The IB508-v2 LED Studio Light is an ultra-lightweight, portable LED lighting solution that features 508 Bi-Color LEDs. The IB508-v2 is powered by the 2 included Sony "L" series batteries, and includes adjustable barn doors with intensifiers, a color temperature orange filter, and a digital readout for brightness and battery life indication.

Popular applications for the CHRB550-v2 include studio and Chroma key applications. The kit includes 5 IB508-v2s, 5 compact light stands, 10 DV Batteries, 5 AC power supplies, 5 battery chargers, 5 diffusers, 5 stand adapters, 1 light bag and 1 light kit bag.



CHRB550-v2 | Kit with 5 x IB508-v2 Studio Lights | UPC Code: 847983011995

Special Features

- Five Light Bi-Color Kit
- Adjustable Barn Doors with Intensifiers
- Digital Readout for Brightness and Battery Life
- Adjust Between 5600K-3200K
- Wide Angle Beam Pattern

Recommended For

- Studio Lighting
- Portrait Photography
- Interviews

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

CHRB550-v2

Features you need, Prices you want.

Adjustable Barndoors

Adjustable barn doors allow for artistic use of your lighting fixture for any situation.

Battery Life

The Kit includes 1- IBS-750 "L" Series Batteries.

Digital Displays

Digital readouts indicate battery life as well as brightness levels during your set.

Multiple Kits Available

IB508-v2 lights are also available individually or in different kit combinations that provide added value that may include stands, bags and other accessories.

What's Included

- 2 x Light Bag (IBG-500-3L)
- 10 x DV Batteries
- 5 x AC Power Supplies
- 5 x Battery Chargers
- 5 x Compact Light Stands
- 5 x Diffusers
- 5 x ID508-v2 Lights
- 5 x Stand Adapters

Specifications

Beam Angle	50°
Build Material	Heavy Duty Plastic & Aluminum
Color Temperature	3200K—5600K
Control	Local Knob
Cooling System	Passive Cooling
Dimming	10-100%
Fixture Size	13 x 6.75 x 1 In.
Fixture Weight	3 lbs
Focusing	N/A
Head Type	Bi-Color
Lens	60 Degree Lens
Light Source	254 0.06watt LED at 5600K 254 0.06watt LED at 3200K
Mount	Stand Mount
Operating Volts	12v to 14.4v
Power Supply	12v @ 3.33amps
Rating	120v @60Hz
Shipping Dimensions	24 x 20 x 14 In.
Shipping Weight	86 lbs

Optional Accessories

- LCGK-2** Large Creative Gel Kit
- IBS-1170** Sony "L" Series Compatible High Capacity Battery
- IBS-970** Sony "L" Series NP-F970 Compatible Battery
- CP-STND** Compact Light Stand

Photometrics

