



## VM-4DT

1:4 4K60 4:2:0 LongReach HDBaseT DA

| HDBaseT



VM4DT is a highquality, longreach 4K@60Hz (4:2:0) HDBaseT extender distributor that takes one longreach HDBaseT input, equalizes and reclocks the signal and distributes it to four identical HDBaseT outputs. VM4DT distributes native HDBaseT signals with up to 4K video resolution, along with their reextension over HDBaseT

## FEATURES

**High Performance Distribution** - Distributes one native, longreach HDBaseT signal to three outputs with up to 4K video resolution, along with their reextension over HDBaseT

**Dual-side Extension** - Extends a 4K@60Hz (4:2:0) 24bpp (maximum) video signal to a distance of up to 40m (130ft) longreach, and even further for lower video resolutions, when deployed midway between an AV source and multiple remote acceptors using CAT copper cable

**Standard Compatibility** - Connects to any HDBaseT compliant extension product on the market

**HDMI Signal Transmission** - HDMI 2.0 and HDCP 1.4 compliant signal, supporting deep color, x.v.Color™, lip sync, 7.1 PCM, Dolby TrueHD, DTSHD, 2K, 4K, and 3D. EDID and CEC (OUT 1 only) signals are passed through from the source to the display

**IEDIDPro™ Kramer Intelligent EDID Processing™** - An intelligent EDID handling, processing and passthrough algorithm that ensures Plug and Play operation for HDMI source and display systems

**LED Indicators** - Status indicators for HDBaseT input/output connected signals and power for ease of maintenance and troubleshooting

**Easy Installation** - Twistedpair cables for HDBaseT signals wiring. Standard halfwidth 19" rack (1U) fanless enclosure for sidebyside mounting of 2 units in a 1U rack space with included rack mountingears



# KRAMER

## TECHNICAL SPECIFICATIONS

---

Input:	1 HDBT on an RJ-45 female connector
Outputs:	4 HDBT on RJ-45 female connectors
Max. Data Rate:	10.2Gbps (3.4Gbps per graphic channel)
Range Extension (Input or Output Each Side):	Up to 40m (130ft) at 4K@60Hz (4:2:0), Up to 70m (230ft) at full HD (1080p @60Hz 36bpp), Note: When using Kramer HDBaseT cables
Max. Video Resolution:	4K@60Hz (4:2:0) 24bpp
Compliance:	Supports HDMI 2.0, HDCP 1.4 and HDBaseT 1.0
Controls:	EDID setup button, indicator LEDs: OUTPUTS 14; LINK 14; active input, power on
Operating Temperature:	0° to +40°C (32° to 104°F)
Storage Temperature:	40° to +70°C (40° to 158°F)
Humidity:	10% to 90%, RHL noncondensing
Power Consumption:	Power source: 5.2V DC, 4A; power consumption: 5V DC, 3.5A
Enclosure:	Desktop size, Aluminum type
Cooling:	Fan ventilation
Product Dimensions:	21.5cm x 16.3cm x 4.4cm (8.4" x 6.4" x 7.2") W, D, H
Product Weight:	0.53kg (1.67lbs) approx
Shipping Dimensions:	31.5cm x 21.2cm x 7.2cm (12.4" x 8.4" x 2.8") W, D, H
Shipping Weight:	1.29kg (2.83lbs) approx
Included Accessories:	Power supply
Options:	RK1 19" rack adapter

