



VGA-IN2-F16

2Channel VGA Input Card

| Kramer Core



VGAIN2F16 is a twochannel VGA input card for the VS1616 Series Modular MultiFormat Digital Matrix Switchers. The VGAIN2F16 inputs two VGA signals into the chassis

FEATURES

- Max bandwidth - 450MHz
- Auto or User-Defined Resolution Detection & Phase Mode
- Adjustable Brightness & Contrast



KRAMER

TECHNICAL SPECIFICATIONS

PORTS:	2 VGA on 15pin HD connectors
BANDWIDTH:	450MHz
MAXIMUM RANGE:	10m (32ft)
POWER CONSUMPTION:	5.5W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
DIMENSIONS:	19cm x 13cm x 2cm (7.5" x 5.1" x 0.8") W, D, H
PRODUCT WEIGHT:	0.23kg (0.51 bs) approx
SHIPPING WEIGHT:	0.37kg (0.82lbs) approx
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE