

FC-69

4K60 4:2:0 HDMI Audio Embedder/DeEmbedder

| HDMI | 4K/60 UHD (4:2:0)



FC69 is a highperformance 4K@60Hz (4:2:0), 4Kx2K HDMI audio embedder and deembedder. The unit can embed analog audio to the HDMI output or deembed audio from the HDMI input or from the HDMI output Audio Return Channel to S/PDIF and unbalanced stereo audio outputs simultaneously

FEATURES

Max. Resolution - 4K@60Hz (4:2:0), 4Kx2K

Max. Data Rate - 8.91Gbps (2.97Gbps per data channel)

HDTV Compatible

HDCP Compliant

HDMI Support - ARC, 7.1 PCM, deep color

Audio Embedding - Even without an HDMI source

Audio de-Embedding - To unbalanced analog and S/PDIF, selectable from input or ARC Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

Sleep Mode - 5V on the output, following the input, allows the display to turn off when no video is being sent

Preconfigured Control Options - DIPswitches control locking/modifying EDID, HDCP, embedding/deembedding and sleep mode functionality



TECHNICAL SPECIFICATIONS

INPUT: 1 HDMI on an HDMI connector, 1 analog stereo audio on a 3.5mm mini jack

OUTPUTS: 1 HDMI on an HDMI connector, 1 S/PDIF digital audio on an RCA connector, 1

analog stereo audio on a 3.5 mm mini jack

MAX DATA RATE: 8.91Gbps (2.97Gbps per graphic channel), 1080p @60Hz, 36bit Deep Color,

supports 4K@60 UHD (4:2:0), 4Kx2K

AUDIO THD+N: -75dB

COMPLIANCE WITH Supports HDMI, HDCP HDMI STANDARD:

CONTROLS: 8way DIPswitch

INDICATOR LEDS: ON, IN, OUT, HDCP

POWER SOURCE: 5V DC, 500mA

OPERATING

0° to +40°C (32° to 104°F)

TEMPERATURE:

STORAGE 40° to +70°C (40° to 158°F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL noncondensing

PRODUCT

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

DIMENSION:

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

SHIPPING DIMENSION:

15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT: 0.5kg (1.0lbs) approx

COOLING: Convection

ENCLOSURE TYPE: Aluminium

RACK MOUNT: With optional adapter

FURNITURE MOUNT: With included rubber feet

VIBRATION: ISTA 1A in carton (International Safe Transit Association)

REGULATORY

COMPLIANCE:

CE

ENVIRONMENTAL REGULATORY

RoHs and WEEE

COMPLIANCE: INCLUDED

Power supply

ACCESSORIES:

OPTIONS: RK3T 19" rack adapter

WARRANTY: 7 years parts and labor

