



KRAMER

PT-101UHD

4K60 4:2:0 HDMI 2.0 HDCP 2.2 Repeater

| HDMI | 4K/60 UHD (4:2:0)
| HDCP 2.2 Compatible



PT101UHD is a highperformance repeater/extender for 4K@60Hz (4:2:0) HDMI 2.0 and HDCP 2.2 signals. The unit can extend the range up to 20m (66ft) for 4K@60Hz (4:2:0) signals

FEATURES

Range Extension - 4K@30Hz (4:2:0) up to 20m (66ft) (15m on the input to the PT-101UHD and 5m on the output)

Max. Data Rate - 10.2Gbps (3.4Gbps per data channel)

Re-clocking and Equalization

HDMI Output Power Follows Input - There is no power on the output when there is no active input

Transparent HDMI 2.x and HDCP 2.2 Support



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------------|--|
| INPUT: | 1 HDMI on an HDMI connector |
| OUTPUT: | 1 HDMI on an HDMI connector |
| BANDWIDTH: | Supports up to 10.2Gbps (3.4Gbps per graphic channel); supports up to 4K@60Hz (4:2:0) including WUXGA and 1080p 36bit Deep Color |
| COMPLIANCE WITH HDMI STANDARD: | HDMI 2.0, HDCP |
| INDICATORS | ON LED indicates power and/or HDMI signal |
| POWER SOURCE: | 5V DC, 230mA |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL noncondensing |
| COOLING: | Convection |
| PRODUCT DIMENSION: | 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H |
| PRODUCT WEIGHT: | 0.1kg (0.2lbs) approx |
| SHIPPING DIMENSION: | 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H |
| SHIPPING WEIGHT: | 0.5kg (1.1lbs) approx |
| ENCLOSURE TYPE: | Aluminium |
| VIBRATION: | ISTA 1A in carton (International Safe Transit Association) |
| REGULATORY COMPLIANCE: | CE |
| ENVIRONMENTAL REGULATORY COMPLIANCE: | RoHs and WEEE |
| INCLUDED ACCESSORIES: | Power supply |
| OPTIONAL ACCESSORIES | RK4PT 19" rack adapter |

