



Yarden 5-O

5.25-Inch, 2-Way On-Wall Speakers

| Speakers



The Yarden 5-O High Performance On-wall Speaker features a Kevlar(R) woofer, 2nd level cross-over design and multi-tap power transformer for selecting 8 (bypassing the transformer) or 70V/100V power settings that are suitable for an array installation

FEATURES

Type - 2way onwall speaker

Woofer - 5.25" Kevlar(R) cone

Tweeter - 0.5" Mylar dome

Impedance - 8

Power Handling - 30W RMS, 80W continuous program

Transformer Taps - 70V: 20W/10W/5W/2.5W/Off (LoZ); 100V: 20W/10W /5W/Off (LoZ)

Package - 2 speakers (1 pair)



KRAMER

TECHNICAL SPECIFICATIONS

DESCRIPTION:	2way onwall speakers
FREQUENCY RESPONSE:	80Hz to 20kHz @10dB, 100Hz to 20kHz @±3dB
WOOFER:	5.25" (133mm) Kevlar(R) with rubber surround
TWEETER:	0.5" (13mm) Mylar
IMPEDANCE:	8 (transformer tap in off position)
TRANSFORMER TAPS:	70V – 20W/10W/5W/2.5W/Off (LoZ), 100V – 20W/10W/5W/Off (LoZ)
SENSITIVITY:	88dB SPL, 1W @1m
MAX SPL:	Continuous:101dB, peak: 104dB
POWER HANDLING:	30W RMS, 80W continuous program
CROSSOVER FREQUENCY:	9kHz
DIRECTIVITY FACTOR (Q):	4 averaged 1kHz to 10kHz
DIRECTIVITY INDEX (DI):	6dB averaged 1kHz to 10kHz
INPUT CONNECTORS:	Terminal blocks
MATERIALS:	Frame, aluminum grill, steel brackets and ABS cabinet
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
WEIGHT PER SINGLE SPEAKER:	2.15kg (4.7lbs) approx
WEIGHT WITH MOUNTING KIT:	2.3kg (5.1lbs) approx
SHIPPING WEIGHT (FOR PAIR):	5.3kg (11.7lbs) approx
INSTALLATION CLEARANCE:	Front panel to wall (with mounting bracket): 18.7 cm (7.4"), back panel to wall (with mounting bracket): 2.4 cm (0.9")
ACCESSORIES:	2 mounting brackets (including 4 knobs and 4 mounting screws)
OPTIONS:	BCP2S speaker cable
COLORS:	Available in white