

## **VCO-5UHD**

5Port 4K60 4:2:0 HDMI Video Content Overlay Solution | HDMI | Ethernet - RJ-45



VCO5UHD is a video content overlay solution that overlays five independent graphic images to any number of displays over standard HDMI in resolutions up to 4K60 (4:2:0). This enables the display of individual, targeted messages for each and every display in your installation

## **FEATURES**

4K60 4:2:0 Overlays - Static or animated, dynamic color image

Overlays Any Size Content - With full transparency control

Multiple Overlay Templates - For multiple applications

Selectable Looping Output - For daisychaining any number of displays

Centralized Control of all Promotional Overlays

Error Reporting - Comprehensive error reporting for connected displays and overlays

Full Overlay Automation - Automates entire overlay process from design to display, in multiple locations

Easy to Use - Featurerich software - design, schedule, and display

Enables Digital Signage with Unlimited Viewing Zones



## **TECHNICAL SPECIFICATIONS**

1 HDMI On a female HDMI connector

1 USB On a female USB TypeA connector

5 HDMI On female HDMI connectors

1 Loop HDMI On a female HDMI connector

Ethernet 10/100BaseT On an RJ-45 connector

PRODUCT 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72" ) W, D, H

DIMENSION:

SHIPPING 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83" ) W, D, H

DIMENSION:

Max Resolution 4K60 (4:2:0)

Controls IP address setup DIP-switches, Reset/Test button, Ethernet (VCO Setup App),

output status indication LEDs, input indication LED, loop indication LED

Consumption 5V DC, 1.6A

Operating  $0^{\circ}$  to  $+40^{\circ}$ C (32° to  $104^{\circ}$ F)

Temperature

Storage Temperature -40° to +70°C (-40° to 158°F)

Humidity 10% to 90%, RHL non-condensing

Included: Power cord, rack ears, cable bracket, plastic cable ties

