



KRAMER

WP-110

Active Wall Plate - Computer Graphics Video Transmitter



The WP-110 is a wall plate transmitter for computer graphics video signals with resolutions up to and exceeding UXGA. It converts a computer graphics video signal into a twisted pair signal that it transmits to the TP-120 receiver or other compatible Kramer receiver

FEATURES

Max. Resolution - WUXGA & 1080p

HDTV Compatible

Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 50m (150ft) of each other. All the system units must have the Power Connect system to use this feature

Advanced Sync Processing - Ensures compatibility with a wide range of computers

Front Panel Connection - 15pin HD (F) input

Rear Panel Connection - RJ45 output

Sync Polarity Settings - H & V switches for improved display compatibility with the CAT 5 outputs

System Range - Up to 100m (320ft)

Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5

Dimensions - 6.9cm x 4.1cm x 11.4cm (2.71" x 1.63" x 4.49") US; 8.6cm x 4.1cm x 8.6cm (3.39" x 1.63" x 3.39") and 8cm x 4.1cm x 8cm (3.15" x 1.63" x 3.15") EU W, D, H

Optional - RK121WP 19" rack adapter (for EU size wall plates only)



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|--|
| INPUT: | 1 VGA/UXGA on a 15pin HD connector |
| OUTPUTS: | 1 RJ45 LINE OUT connector |
| MAX. RESOLUTION: | WUXGA & 1080p |
| DIFF. GAIN: | 2.9% (worst case) |
| DIFF. PHASE: | 0.3Deg (worst case) |
| K-FACTOR: | <0.05% |
| S/N RATIO: | 70dB (worst case) |
| COUPLING: | AC |
| POWER CONSUMPTION: | 12V DC, 60mA |
| OPTIONS: | RK121WP 19" rack adapter |
| PRODUCT DIMENSION: | 8.60cm x 3.60cm x 8.60cm (3.39" x 1.42" x 3.39") W, D, H |
| PRODUCT WEIGHT: | 0.1kg (0.2lbs) approx |
| SHIPPING DIMENSION: | 8.00cm x 10.00cm x 5.80cm (3.15" x 3.94" x 2.28") W, D, H |
| SHIPPING WEIGHT: | 0.4kg (0.8lbs) approx |
| INCLUDED ACCESSORIES: | Power supply |