



KRAMER

VP-426H2

4K60 4:4:4 HDCP 2.2 HDMI 2.0 / VGA Scaler

| HDMI | HDCP 2.2 Compatible



VP426H2 is a highperformance digital scaler for HDMI and computer graphics/HDTV signals. The unit up or downscales computer graphics and HDTV signals to resolutions up to 4Kx2K. 28 output resolutions and native are supported. The user selects the computer graphics/HDTV or HDMI input and the scaled output is sent to both the computer graphics and HDMI outputs

FEATURES

- Max. Resolution - 4K@60Hz (4:4:4)
- Standards Compliance - HDMI 2.0, HDCP 2.2/1.4
- EDID Handling - Reading and storage of acceptor's EDID
- Inputs - VGA (RGBHV), Component (YPrPr) or HDMI
- Outputs - Simultaneous RGBHV and HDMI
- Input Auto-Scanning
- Constant Sync - Maintains sync on the output, even if input video signal is lost or interrupted
- Analog/Embedded Audio Support - For inputs and outputs
- Built-in ProcAmp - For convenient signal adjustment
- On-Screen Display (OSD) - For easy setup and adjustment, accessible via the frontpanel buttons
- Non-Volatile Memory - Retains last settings used
- Freeze Button
- Contact Closure - For remote switching of sources
- USB Port - For upgrading firmware



KRAMER

TECHNICAL SPECIFICATIONS

1 PC/HD (RGBHV/YPbPr): on a 15pin HD connector

1 HDMI: on a female HDMI connector

2 unbalanced stereo audio connectors: on 3.5mm mini jacks

1 PC (RGBHV): on a 15pin HD connector

1 HDMI: on a female HDMI connector

1 unbalanced stereo audio: on a 3.5mm mini jack

Output Resolutions:

PRODUCT DIMENSION: 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H

PRODUCT WEIGHT: 0.5kg (1.1lbs) approx

SHIPPING DIMENSION: 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

SHIPPING WEIGHT: 1.0kg (2.2lbs) approx

For the HDMI and VGA outputs: 640x480@60Hz, 800x600@60Hz 1024x768@60Hz, 1280x768@60Hz, 1360x768@60Hz, 1280x800@60Hz, 1280x1024@60Hz, 1440x900@60Hz, 1400x1050@60Hz, 1680x1050@60Hz, 1600x1200@60Hz, 1920x1200 RB@60Hz

For the HDMI output only: 480P@60Hz, 576P@50Hz, 720P@50/60Hz, 1080P@24/25/30/50/60Hz, 4k2k@24/25/30/50/60Hz, 4k2k (4:2:0)@50/60Hz

Output Refresh Rate: 60Hz for computer graphics resolutions, 50/60Hz for HDTV resolutions

Latency: Progressive input: 30ms (approx.), interlaced input: 50ms (approx.)

Sampling Rate: 44.1kHz, 48kHz for analog audio output

Controls: Front panel buttons, 1 remote contact closure on a 3pin terminal block connector, 1 USB for programming

Indicators: ON, HDMI and PC LEDs

Source 5V DC

Consumption: 1.2A

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: 40° to +70°C (40° to 158°F)

Humidity: 10% to 90%, RHL noncondensing

Included: Power supply (5.2V/4A), bracket set

Optional: RKT2B 19" rack adapter

