

RC-62

6button KNET™ Control Keypad (EU, UK, US)



The RC62 is a 6button room controller for multimedia rooms. The unit can control audio components, video components and other room facilities such as lights and screens

FEATURES

Back Lit & Label Capable Buttons - 6 RGBcolor, tactile feedback, backlit buttons. Buttons are grouped in 2 groups, 4 buttons in 'SOURCES' group, and 2 buttons in 'DISPLAY' group

Custom Labeled, Removable Button Caps

2 K-NET™ Connectors - Connects to master room controller, and auxiliary keypads for remote keypad control

K-NET™ Single Link Connection - Provides a single keypad link cableconnectivity, carrying both power and keypad control communication information

RS-232 Control Port - Controls a device via serial control protocols

IR Emitter Control Port - Controls a device via IR control protocols

Relay Control Port - Controls a device via relay contact closure

IR Sensor Port - Learns commands from IR remotes

Program Control - Program configuration with Kramer KConfig software

Keypad Lock-Out - Option for tampering prevention by locking and unlocking of the keypad buttons

Mini USB Port - To upload configuration files, set the KNET™ ID number, and power the device during configuration

Mounting - Inwall, in standard 2 gang EU, UK, and 1 Gang US wall junction boxes

Easy Installation - Fits to standard inwall boxes for simple and costreducing installation



TECHNICAL SPECIFICATIONS

PORTS: 1 RS232 on terminal block connectors; 2 KNET on terminal block connectors; 1

USB port

OUTPUTS: 2 relays on terminal block connectors (36V AC or DC, 2A, 60V AC maximum on

noninductive load); 1 IR emitter on terminal block connectors

POWER 12V DC, 100mA

CONSUMPTION:

ADAPTER: SummitView™ kits: 12V, 5A; independent: 12V/500mA

OPERATING 0° to +40°C (32° to 104°F)

TEMPERATURE:

STORAGE 40° to +70°C (40° to 158°F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL noncondensing

PRODUCT DIMENSION:

6.90cm x 3.40cm x 11.43cm (2.72" x 1.34" x 4.50") W, D, H

PRODUCT WEIGHT: 0.1kg (0.2lbs) approx

SHIPPING 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.6kg (1.2lbs) approx

INCLUDED Label set, screwdriver

ACCESSORIES:

OPTIONS: Power supply, RK121WP 19" rack adapter



CONFIGURATIONS

| RC-62/EU(W)-86 | UK-size RC-62, White Design Frame, PSU + Power cord, Label Set, Screwdriver |
|----------------|---|
| RC-62/EU(B)-86 | UK-size RC-62, Black Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-62/EU(W)-80 | EU-size RC-62, White Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-62/EU(B)-80 | EU-size RC-62, Black Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-62(W) | US-size RC-62, White Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-62/JP(W) | US-size RC-62, White Design Frame, PSU + Japan Power cord, Label Set, Screwdriver |
| RC-62(B) | US-size RC-62, Black Design Frame, PSU + Power cord, Label Set, Screwdriver |
| RC-62/JP(B) | US-size RC-62, Black Design Frame, PSU + Japan Power cord, Label Set, Screwdriver |

