




KRAMER

RC-63A

6button KNET™ Control Keypad with Knob
(EU, UK, US)



The RC63AL is a 6button room controller with an analog volume knob for multimedia rooms. The unit can control audio components, video components and other room facilities such as lights and screens

FEATURES

Back Lit & Label Capable Buttons - 6 RGBcolor, tactile feedback, backlit buttons. Buttons are grouped in 2 groups, 4 buttons in 'SOURCES' group, and 2 buttons in 'DISPLAY' group

Custom Labeled, Removable Button Caps

Analog Knob - Controls volume adjustments via bidirectional rotating 10Vrange knob

2 K-NET™ Connectors - Connects to master room controller, and auxiliary keypads for remote keypad control

K-NET™ Single Link Connection - Provides a single keypad link cableconnectivity, carrying both power and keypad control communication information

RS-232 Control Port - Controls a device via serial control protocols

IR Emitter Control Port - Controls a device via IR control protocols

Relay Control Port - Controls a device via relay contact closure

IR Sensor Port - Learns commands from IR remotes

Program Control - Program configuration with Kramer KConfig software

Keypad Lock-Out - Option for tampering prevention by locking and unlocking of the keypad buttons

Mini USB Port - For uploading configuration files, setting the KNET™ ID number, and powering the device during configuration

Mounting - Inwall, in standard 2 gang EU, UK, and US wall junction boxes

Easy Installation - Fits standard inwall boxes for simple and costreducing installation



KRAMER

TECHNICAL SPECIFICATIONS

PORTS:	1 RS232 on terminal block connectors, 2 KNET on terminal block connectors, 1 Mini USB for programming
OUTPUT:	2 relays on terminal block connectors (36V AC or DC, 2A, 60V AC maximum on noninductive load), 1 IR emitter on terminal block connectors
POWER CONSUMPTION:	12V DC, 100mA
FUSE:	500mA, FSMD 2920
ADAPTER:	SummitView™ kits: 12V, 5A; independent: 12V, 500mA
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
PRODUCT DIMENSION:	11.43cm x 2.50cm x 11.43cm (4.50" x 0.98" x 4.50") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H
SHIPPING WEIGHT:	0.6kg (1.2lbs) approx
INCLUDED ACCESSORIES:	Power supply, label set, screwdriver
OPTIONS:	RK121WP 19" rack adapter



KRAMER

CONFIGURATIONS

RC-63A/EU(W)-86	UK-size RC-63A, White Design Frame, PSU + Power Cord, Label Set, Screwdriver
RC-63A/EU(B)-86	UK-size RC-63A, Black Design Frame, PSU + Power Cord, Label Set, Screwdriver
RC-63A/EU(W)-80	EU-size RC-63A, White Design Frame, PSU + Power Cord, Label Set, Screwdriver
RC-63A/EU(B)-80	EU-size RC-63A, Black Design Frame, PSU + Power Cord, Label Set, Screwdriver
RC-63A(W)	US-size RC-63A, White Design Frame, PSU + Power Cord, Label Set, Screwdriver
RC-63A(W)/JP	US-size RC-63A, White Design Frame, PSU + Power Cord, Label Set, Screwdriver
RC-63A(B)	US-size RC-63A, Black Design Frame, PSU + Power Cord, Label Set, Screwdriver
RC-63A(B)/JP	US-size RC-63A, Black Design Frame, PSU + Power Cord, Label Set, Screwdriver