



kramer

KDock-2

USB-C Hub Multiport Adapter



KDock-2 is a USB-C hub multiport adapter specially designed to support mobile devices and is an ideal accessory for MacBook, laptops equipped with USB Type-C, smartphones, and tablets. KDock-2 enables you to connect your USB-C device to an HDMI™ video output, 2 USB 3.0 ports, an Ethernet port, SD card port and USB-C port for data transmission and charging.

Note: Video output for smartphones is supported only for smartphones that support DisplayPort Alt mode through USB-C

TECHNICAL SPECIFICATIONS

Inputs	1 USB: On a USB Type-C male connector
Outputs	1 HDMI On a female HDMI connector.:
Ports	2 USB 3.0: On female USB type-A connectors 1 Ethernet: On an RJ-45 connector SD: On an SD card port 1 USB: On a female USB type-C connector for data and charging
Video	Max Resolution (HDMI output): 3840x2160P@30Hz Max Data Rate: (HDMI output): 10.2Gbps (3.4Gbps per graphic channel) Content Protection (HDMI output): HDCP 1.4
Extended Ethernet	Max Data Rate 1000M (Gigabit)/100M/10M Includes Wake-on-LAN (WoL), single Mac address, PXE boot
General	USB Data Transmission Speed (USB 3.0 & USB-C) up to 5.0Gbps
Power	Delivery 100W USB Charging: BC1.2 (5V 1.5A) USB Limited Current when Connected to Power via female USB-C port: 1.9A USB Limited Current when Not Connected to Power via female USB-C port: 1A
Environmental Conditions	Operating Temperature: 0° to +70°C (32° to 158°F) Storage Temperature: -10° to +55°C (14° to 131°F) Humidity: 5% to 90%, RHL non-condensing
Enclosure	Type: Aluminum with built-in 16cm/6.3" flexible USB-C cable
Regulatory Compliance (Standards Compliance)	Safety: CE Environmental: RoHs, FCC

Product Dimensions 11.65cm x 6.68cm x 1.60cm (4.59" x 2.63" x 0.63") W, D, H

Product Weight 0.1kg (0.2lbs) approx

Shipping Dimensions 15.60cm x 10.20cm x 3.50cm (6.14" x 4.02" x 1.38") W, D, H

Shipping Weight 0.1kg (0.3lbs) approx

