



VM-22H

2x1:2 Compact HDMI Switchable DA

| HDMI | HDCP Compliant



The VM-22H is a distribution amplifier for HDMI signals. The unit reclocks and equalizes one of two selectable input signals and distributes it to two identical outputs

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)
- HDCP Compliant
- HDMI Support - Deep Color, x.v.Color™, Lip Sync, CEC
- 3D Pass-Through
- EDID Pass-through - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems
- Active Output LED Indicators
- Control - Front panel or IR remote switching
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors
OUTPUTS:	2 HDMI connectors
BANDWIDTH:	6.75Gbps (2.25Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP
CONTROLS:	EDID SETUP button, input select button, IR
INDICATOR LEDs:	IN 1, IN 2, OUT 1, OUT 2, and ON LEDs
POWER CONSUMPTION:	5V DC, 910mA
INCLUDED ACCESSORIES:	Power supply, bracket installation kit
OPTIONS:	HDMI/HDMI male-to-male cables
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
Product Weight	0.3kg (0.7lbs) approx
Shipping Dimensions	49.00cm x 18.60cm x 58.80cm (19.29" x 7.32" x 23.15") W, D, H
Shipping Weight	0.6kg (1.2lbs) approx

