



VCO-1

Single Port HDMI Video Content Overlay Solution

| HDMI | Ethernet - RJ-45



The VCO1 is a video content overlay solution that overlays one independent graphic image to any number of displays over standard HDMI in full HD – 1080p/60 or 1920x1200 resolution. This allows the display of individual, targeted messages for each and every display in your installation

FEATURES

- Full HD Overlays - Static or animated, dynamic color image
- Overlays Any Size Content with Full Transparency Control
- Multiple Overlay Templates - For multiple applications
- Built-in Looping Output - For daisy chaining any number of displays
- Centralized Control of all Promotional Overlays
- Support for Unlimited Number of Overlays and Displays
- Error Reporting - Comprehensive error reporting for connected displays and overlays
- Full Overlay Automation - Automates entire overlay process from design to display, in multiple locations
- Easy to Use - Feature-rich software – design, schedule, and display
- Enables Digital Signage with Unlimited Viewing Zones



KRAMER

TECHNICAL SPECIFICATIONS

Inputs:	1 HDMI connector (HDMI, HDCP version 1.4), 1 USB port
Outputs:	1 HDMI connector (HDMI, HDCP version 1.4)
Ports:	1 RJ-45 Ethernet port 10/100BaseT
Bandwidth:	Full HD resolution (1080p60 or 1920x1200)
Controls:	IP address setup DIP-switches, Reset/Test button, Ethernet (VCO Setup App), output status indication LEDs, input indication LED
Power Consumption:	5V DC, 800mA max
Operating Temperature:	0° to +40°C (32° to 104°F)
Storage Temperature:	-40° to +70°C (-40° to 158°F)
Humidity:	10% to 90%, RHL non-condensing
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.3kg (0.6lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.7kg (1.5lbs) approx
Included Accessories:	Power supply unit (5V DC, 4A)

