



KRAMER

VCO-16

16Port HDMI Video Content Overlay Solution

| HDMI | Ethernet - RJ-45



The VCO16 is a video content overlay solution that overlays sixteen independent graphic image to any number of displays over standard HDMI in full HD – 1080p/60 or 1920x1200 resolution. This allows the display of individual, targeted messages for each and every display in your installation

FEATURES

- Full HD Overlays - Static or animated, dynamic color image
- Overlays Any Size Content with Full Transparency Control
- Multiple Overlay Templates - For multiple applications
- Built-in Looping Output - For daisy chaining any number of displays
- Centralized Control of all Promotional Overlays
- Support for Unlimited Number of Overlays and Displays
- Error Reporting - Comprehensive error reporting for connected displays and overlays
- Full Overlay Automation - Automates entire overlay process from design to display, in multiple locations
- Easy to Use - Feature-rich software – design, schedule, and display
- Enables Digital Signage with Unlimited Viewing Zones



KRAMER

TECHNICAL SPECIFICATIONS

Inputs:	1 HDMI connector (HDMI, HDCP version 1.4), 1 USB port
Outputs:	16 HDMI connectors (HDMI, HDCP version 1.4), 1 LOOP HDMI connector
Ports:	1 RJ-45 Ethernet port 10/100BaseT
Bandwidth:	Full HD resolution (1080p60 or 1920x1200)
Controls:	IP address setup DIP-switches, Reset/Test button, Ethernet (VCO Setup App), output status indication LEDs, input indication LED, loop indication LED (for VCO-8 and VCO-16 only)
Power Consumption:	100-240V AC, 32VA max
Operating Temperature:	0° to +40°C (32° to 104°F)
Storage Temperature:	-40° to +70°C (-40° to 158°F)
Humidity:	10% to 90%, RHL non-condensing
PRODUCT DIMENSION:	19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H
PRODUCT WEIGHT:	1.7kg (3.8lbs) approx
SHIPPING DIMENSION:	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H
SHIPPING WEIGHT:	2.6kg (5.7lbs) approx
Included Accessories:	Power cord, rack ears, cable bracket, cable plastic ties

