


MECHANICAL DETAILS

- Shell Style Model** FG* : Straight plug cable collet
- Keying** 1 key (alpha=0, plug: male contacts, receptacle: female contacts)
- Housing Material** Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
- Cable Fixing** 2.3 - 2.7 mm
- Variant 2** Z : Nut for fitting a bend relief

	A	L	M	S1	S2
Mm	6.4	28.5	20.7	5.5	6
In.	0.25	1.12	0.81	0.22	0.24



PERFORMANCE DETAIL

- Insert** 0.304 : 4 Low Voltage
- Insulator** L: PEEK (UL 94 / V-0/3.2, depends on material thickness)

Specifications

- Contact Type:** Solder
- Max. Matings:** 5000
- Contact Dia.:** 0.5 mm (0.02in)
- Bucket Dia.:** 0.4 mm (0.016in)
- Max. Solid** 0.09 mm² (AWG 28)
- Max. Stranded** 0.05 mm² (AWG 30)
- R (max):** 8.7 mOhm



OTHER CHARACTERISTICS

- Shell Style/Model** Libellé
- IP Rating** 50









Available Download



unipole_multipole.pdf

Related links

-  [Contact](#)
-  [Quote Request](#)
-  [Catalogs Downloads](#)
-  [Catalogs Requests](#)
-  [Sample Request](#)
-  [3D drawings](#)