

SSPC20A-NC DATASHEET

The Laird SSPC20A-NC series of AC power extension cables is designed to provide reliable AC power extension solutions in the most demanding environments. The series features the rugged SJOOW Laird PWR-12/3-TP power cable terminated to a fully insulated heavy-duty Leviton rubberized quad box that is shock, impact, and corrosion resistant. This series is ideal for Movie and TV production, Rentals, Theaters, Concert touring, Live events, and Industrial maintenance. Available in a variety of standard lengths, in both 15-amp and 20-amp variations.

Features:

- Fully Insulated Heavy-duty Leviton Rubberized Quad Box
- Laird's Flexible and Durable PWR-12/3-TP SJOOW power cable
- Resistant to shock, impact, and corrosion elements



SSPC20A-NC DATASHEET

Specifications:

Overall Specifications:

- **Rubber Quad Box Dimensions:** 3.38" x 2.5" x 3.9"
- **Output:**
 - x4 NEMA 20-amp outlets

Laird PWR-12/3-TP:

- **Cable Type:** SJOOW
- **Number of Conductors x AWG:** 3x12
- **Conductor Insulation:** Rubber (EPR)
- **Outer Jacket Material:** Rubber (CPE)
- **Current Carrying Capacity:** 25 Amps
- **Outer Diameter:** 0.425in – 0.476in
- **Nom. Voltage:** AC U 300V
- **Temperature:**
 - Flexing: -4°F to 194°F (-20°C to +90°C)
 - Static: -40°F to 194°F (-40°C to +90°C)
- **Min Bend Radius:**
 - Flexing: 4.76in
 - Static: 2.85in

Eaton Outlets:

- **Amperage Rating:** 20 Amps
- **Voltage Rating:** 125 Volts

Leviton Plugs:

- **Amperage Rating:** 20 Amps
- **Voltage Rating:** 125 VAC
- **Dielectric Voltage:** Withstands 2000V per UL498