

HDBNC1505 Cable

Video Coax HDBNC to BNC Assemblies

Built with high quality Belden indoor/outdoor BNC cable for fixed and cable reel deployment in studios, OB trucks, and live events with true 75 Ohm impedance for higher performance.

- Space Saving, Low Profile Assembly
- Push & Turn Connector Interface
- Positive Lock for Quick & Guaranteed Mating
- Connectors Anti-Splay Outside Diameter
- SMPTE 292M & SMPTE 424M Compliant
- Terminated with Amphenol HD BNC Connectors

Specifications

- 20 AWG Cable with PVC Outer Jacket
- Gas-injected FHDPE Insulation
- Conductor Material: BC - Bare Copper
- Characteristic Impedance: 75 Ohm
- Outer Shield Material: Dual Shield - Bonded Duofoil/Tinned Copper
- Plenum (Y/N): N
- Nom. Characteristic Impedance: 75 +/- 1.50
- Nom. Conductor DCR: 10 Ohm/1000ft
- Nom. Outer Shield DCR: 3.8 Ohm/1000ft
- Nom. Capacitance Cond-to-Shield: 16.3 pF/ft
- Nom. Impedance: 75 Ohm
- Sustainability: CA Prop 65
- Flammability/Fire Resistance: UL1666 Vertical Shaft, FT4
- Return Loss: 30dB @ 3Ghz
- Data Rate: 3 Gbps or Higher

Export Information

Country of Origin: USA

US ECCN: EAR99

HTS Code: 8544.42

US Dept. of Commerce CCATS: N.a



Mount Marion, NY • 12456

sales@lairddigitalcinema.com • 800-898-0759

www.lairddigitalcinema.com