

MB-MB Video Cable Series

75 Ohm BNC Miniature Coax Assemblies

Low profile, true 75 Ohm BNC cable assemblies built with Belden 9221 miniature coaxial cable and Amphenol BNC connectors.

Features

- Nickel Over Brass Construction for Longevity & Reliability
- Gold Plated Center Pin Offers Corrosion Resistance
- Crimps Tight Every Time For Superior Cable Pull Strength
- Crimp Center Pin and Crimp Collar



Available Lengths in Feet: 2, 3, 6, 10, 15, 25, 50, 100

Amphenol Connector

- Orientation: Straight
- Termination Style: Cable - Crimp
- Impedance: 75 Ohms
- Body Finish: Nickel
- Body Material: Brass
- Contact Finish: Gold
- Contact Material: Brass
- Contact Termination Style: Crimp
- Insulator Material: Delrin
- Coupling Mechanism: Bayonet
- Max Frequency (GHz): 4
- Polarity: Standard
- Min. Temp. (Celsius): -40
- Max. Temp. (Celsius): 85
- Mating Cycles: 500

Belden Cable

- 30 AWG, Stranded
- Ultra-miniature 59/U Type
- .012 Tinned Copper Conductor
- Tinned Copper Braid Shield (90% Coverage)
- Foam HDPE Insulation
- PVC Jacket
- Nom. Capacitance: 17.3 pF/ft
- Nom. Inductance: 0.097 μ H/ft
- Nom. Impedance: 75 Ohms

Mount Marion, NY • 12456

sales@lairddigitalcinema.com • 800-898-0759

www.lairddigitalcinema.com