



MB-MBF Video Cable Series

Male to Female BNC

75 Ohm BNC Miniature Coax Assemblies

Low profile, true 75 Ohm BNC cable assemblies built with Belden 9221 miniature coaxial cable and Amphenol BNC connectors.

Features

- Nickel Over Brass Construction for Longevity & Reliability
- Gold Plated Center Pin Offers Corrosion Resistance
- Crimps Tight Every Time For Superior Cable Pull Strength
- Crimp Center Pin and Crimp Collar



Available Lengths in Feet: 3, 6, 10, 15

Amphenol Connector

- Orientation: Straight
- Termination Style: Cable - Crimp
- Impedance: 75 Ohms
- Body Finish: Nickel
- Body Material: Brass
- Contact Finish: Gold
- Contact Material: Brass
- Contact Termination Style: Crimp
- Insulator Material: Delrin
- Coupling Mechanism: Bayonet
- Max Frequency (GHz): 4
- Polarity: Standard
- Min. Temp. (Celsius): -40
- Max. Temp. (Celsius): 85
- Mating Cycles: 500

Belden Cable

- 30 AWG, Stranded
- Ultra-miniature 59/U Type
- .012 Tinned Copper Conductor
- Tinned Copper Braid Shield (90% Coverage)
- Foam HDPE Insulation
- PVC Jacket
- Nom. Capacitance: 17.3 pF/ft
- Nom. Inductance: 0.097 μ H/ft
- Nom. Impedance: 75 Ohms

Mount Marion, NY • 12456

sales@lairddigitalcinema.com • 800-898-0759

www.lairddigitalcinema.com