



**Product Overview:**

This deceptively simple looking loop acts as a wireless connection to hearing aids equipped with a "T" coil. Listeners hook the loop into their wireless receiver, slip the loop around their neck, and the "T" coil picks up the sound and amplifies the transmitted sound into the ear.

**Highlights:**

- Use with any hearing aid equipped with a "T" coil
- Use with any Listen's receivers
- The receiver's antenna is built into the headphone cord

**Includes:**

One (1) LA-166 Neck Loop

Product Specification: Neck Loop	
<b>Compliance</b>	
Safety	RoHS
Standards	IEC 60118-4
<b>Audio</b>	
Frequency Response	20 Hz - 20 kHz
Impedance	12 ohm +/- 15% @ 1 kHz
Rated Power Input	75 mW
Max Power Input	2 W
Headset Input Sensitivity	110 dB +/- 4dB @ 1 kHz, 1 mW
Magnetic Field Strength	100 mA/m 6 inches above loop at 85µW 1kHz input (IEC 60118-4)
<b>Loop</b>	
Loop Cable Length	33 in. (84 cm)
<b>Interconnections</b>	

LA-166  
Neck Loop

Connectors	3.5 mm Stereo
<b>Physical</b>	
Cable Length	22 in. (55 cm)
Color	Dark Grey
Dimensions (H x W x D)	1.44 in. x 1.10 in. x 0.59 in. (35 mm x 28 mm x 15 mm)
Weight	1.65 oz. (47 g)
Shipping Weight	1 lb. (0.5 kg)