


| | |
|--|---|
| Product Specifications | Part Number: 74-037-01 |
| HDBT Rx | Model: RHB-350 (Rx) |
| Product Image | Product Drawing |
|  |  |
| Features and Benefits (for the matching THB-350) | Mechanical |
| <ul style="list-style-type: none"> > Universal interface, compatible with all source signal formats > World's smallest high performance all purpose signal converter, scaler, switcher, splitter, mixer, HDCP compliant > VGA, HDMI, DP input, auto switch or front panel, RS-232, contact controllable with discrete input LED indications > Configurable display power controls via RS-232 enables fully auto operation systems without any 3rd party controller > Independent analog audio input, can be coupled with any video input, mixed with audio de-embedded from HDMI or DP outputs to bal/unbal analog output, or embedded to HDMI > Dual mirrored outputs, HDBT for big screen/projector and HDMI for local monitor, with or without OSD or screensaver, enable monitor sleep/wake up (energy saving) > Unique RS-232 controlled picture zoom (out) adjustments > HDBT output sending signals up to 70 m (235') with POC > RS-232 selectable video resolutions of common 16:9, 16:10, 4:3 or pixel to pixel modes > High efficiency fanless design for ultimate reliability > Rack mountable, under-table mountable, above-projector mountable metal enclosures | <p>Enclosure material: steel Enclosure size: 4.29" x 1.00" x 3.00" (10.9 x 2.5 x 7.6 cm)</p> |
| Package | Electrical |
| <p>One piece in one color cardboard box; with captive screw plugs and quick start guide no power supply</p>  <p>Box size: 5.9" x 4.8" x 1.1" (15.0 x 12.2 x 2.8 cm) Weight: package, 0.63 lb (0.29kg); product, 0.49 lb (0.22kg) 30-pc box size: 12.4" x 11.6" x 9.5" (31.5 x 29.5 x 24 cm) 30-pc box weight: 21 lb (9.6 kg)</p> | <p>Video output resolution presets: 720p, 1080p, 1280x800, 1920x1200, 1024x768, 1280x960, 1600x1200, pixel to pixel HDBT input: up to 70 m (235') with Cat6 cable; POC 24 V</p> |
| Connections | |
| <p>Input connectors: 1 HDBT Output connector: 1 HDMI Power connector: 2-pin 3.5 mm captive screw receptacle Control connectors: (1) 3-pin RS-232</p> | <p>Controls: Front panel button toggle thru all 3 inputs RS-232 on 3-pin 3.5 mm captive screw, 9600/8-N-1 Contact port on 4-pin 3.5 mm captive screw, discrete pin for each input, dual function (switch to select, LED for indication)</p> |
| Other Related Products | |
| <p>Power supply, 100-240 V in on US plug, 24 V out, P/N 69-008-01</p>  <p>Under desk mount, P/N 78-002-01</p>  <p>HDBT Tx, P/N 74-040-01, model THB-350</p>  | <p>Power consumption: 24 V DC, up to 1 A Optional power supply: Not included. Luxi 69-008-01 Auto switching 100-240 V AC input on US plug, 24 V DC 1 A max on bare wires, wall ward type, UL, PSE, CE, FCC Mounting: Not included. Luxi under desk mount 78-002-01 compatible with several Extron and Middle Atlantic mounts Regulatory compliance Safety: CE, cUL, UL (power supply only) EMI/EMC: CE, FCC Class A MTBF: 30,000 hours Warranty: 3 years parts and labor</p> |