### PCD Series

### plastic cable ducts

#### cost effective solution for open racks

# features

- Available in 1½", 2", 3", and 4" widths
- Available in 3" and 4" depths, single channel and 6" and 8" depths dual channel
- Slotted finger design allows for horizontal cable access exactly where it's needed
- Includes mounting hardware
- Also available as raw duct without mounting ears (1.5" width)
- Fingers can be easily removed to create larger openings
- Hinged plastic covers provide organization while keeping cables hidden
- Ideal for medium to low density installations
- Can be mounted in-between racks for 38 space and higher



PCD shown on RLA series 2 post rack

# pecifications;

PCD Series Plastic Cable Duct shall be Middle Atlantic Products model # PCD-\_\_ (refer to chart). PCD shall be constructed of interior grade rigid PVC and include a hinged plastic cover. PCD shall dimensions shall be \_"H x \_"D x \_"W (refer to chart). PCD shall comply with requirements of RoHS EU Directive 2002/95/EC. PCD shall be manufactured by an ISO 9001 and ISO 14001 registered company. PCD shall be warrantied to be free from defects in material and workmanship under normal use and conditions for the lifetime of the product.

Customizable specification clips available at middleatlantic.com



## PCD Series basic dimensions

PCD SERIES DUAL	A LENGTH (IN)	B WIDTH (IN)	C HEIGHT (IN)
PCD-3-6-38DC	68 [1727.2]	3 [76.2]	6.06 [153.92]
PCD-3-6-45DC	80 [2032]	3 [76.2]	6.06 [153.92]
PCD-4-8-38DC	68 [1727.2]	4 [101.6]	8.06 [204.72]
PCD-4-8-45DC	80 [2032]	4 [101.6]	8.06 [204.72]
PCD-4-8-51DC	92 [2336.8]	4 [101.6]	8.06 [204.72]

PCD DUAL WITH COVER	PCD DUAL WITHOUT COVER
FULL LENGTH STEEL BACKING FOR ADDED STRENGTH	USER INSTALLED BRACKET FOR MOUNTING IN-BETWEEN TWO RACKS (4 PLACES)
	A A S S S S S S S S S S S S S S S S S S
	c

PCD SERIES SINGLE	A LENGTH (IN)	B WIDTH (IN)	C HEIGHT (IN)
PCD-2-3-38SC	68 [1727.2]	2 [50.8]	3.06 [77.72]
PCD-2-3-45SC	80 [2032]	2 [50.8]	3.06 [77.72]
PCD-3-3-38SC	68 [1727.2]	3 [76.2]	3.06 [77.72]
PCD-3-3-45SC	80 [2032]	3 [76.2]	3.06 [77.72]
PCD-4-4-38SC	68 [1727.2]	4 [101.6]	4.06 [103.12]
PCD-4-4-45SC	80 [2032]	4 [101.6]	4.06 [103.12]
PCD-4-4-51SC	92 [2336.8]	4 [101.6]	4.06 [103.12]


PCD SINGLE WITH COVER

PCD SINGLE WITHOUT COVER

TOD CHALL WITHOUT COVER	. 05 0022 00 12
FULL LENGTH STEEL BACKING- FOR ADDED STRENGTH	—USER INSTALLED BRACKET (3" AND 4" WIDTHS) FOR MOUNTING IN-BETWEEN TWO RACKS (4 PLACES)
B C	Ъ

PCD SERIES SINGLE	A LENGTH (IN)	B WIDTH (IN)	C HEIGHT (IN)
PCD-2-3-30SC*	56 [1422.4]	2 [50.8]	3.06 [77.72]
PCD-1.5-2-4BK**	72 [1828.8]	1.5 [38.1]	2.00 [50.80]
PCD-1.5-4-4BK**	72 [1828.8]	1.5 [38.1]	4.00 [101.60]

\* DOES NOT INCLUDE BRACKETS, INCLUDES MOUNTING HARDWARE.
\*\* DOES NOT INCLUDE BRACKETS, DOES NOT INCLUDE MOUNTING
HARDWARE, INCLUDES 4 PIECES



what **great systems** are built on.™

