



FEATURES

- Mitchell base for flat mounting.
- One stage alloy rotary lock leg extension for heavy duty clamping.
- Heavy duty clear anodised alloy tubing.
- Robust glass-filled polymer brackets.
- Suited for HD ground spreader.
- Integrated stainless steel foot spikes.
- Integrated transport clips to pack system down securely.
- 3 year warranty.

*Pictured with #2130 HD Ground Spreader.

Mitchell Base Tripod with Rotary Locking

SPECIFICATIONS

Weight:	5.9 kg (13.2 lbs)
Payload capacity:	95.0 kg (210.0 lbs)
Height range:	737 - 1549 mm (29.0 - 61.0")
Mounting base:	Mitchell base
Transport length:	946 mm (37.2")*
Footprint diameter:	866 - 1346 mm (34.1 - 52.9")*
Leg extension:	1 stage
Lock type:	Rotary lock
Leg material:	Alloy
Warranty:	3 Years

OPTIONAL ACCESSORIES

480	Studio dolly
481	Studio dolly with cable guards
483	Studio tracker dolly
318	Hardcase

*Includes #2130 HD Ground Spreader.



Quality
ISO 9001

SAI GLOBAL

AUSTRALIA

Miller Camera Support Equipment
30 Hotham Parade
Artarmon, Sydney, NSW 2064
Australia

P +61 2 9439 6377 F +61 2 9438 2819
sales@miller.com.au

EUROPE

Miller Fluid Heads (Europe) Ltd.
Unit 12A, Shepperton Business Park
Govett Avenue, Shepperton
Middlesex, TW17 8BA
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
sales@millertripods-europe.com

USA

Miller Camera Support LLC
216 Little Falls Road (Unit 15 & 16),
Cedar Grove, New Jersey 07009
USA

P +1 (973) 857 8300 F +1 (973) 857 8188
sales@millertripods.us