



## FEATURES

- 100mm alloy bowl.
- 2 stage fast toggle adjustment legs.
- Durable black anodised alloy tubing.
- Flip out transport clips.
- Suited for above ground spreader.
- Integrated stainless steel foot spikes.
- Stay flat rubber feet (optional).
- Three-year warranty.

\*Pictured with Rubber Feet (550) and Above Ground Spreader (508)

## Affordable, Light Weight Performer

### SPECIFICATIONS

Weight:	2.5 kg (5.5 lbs)
Payload capacity:	25.0 kg (55.0 lbs)
Height range:	620 - 1330 mm (24.4 - 52.4")
Bowl diameter:	75 mm (2.9")
Transport length:	830 mm (32.7")
Leg extension:	2 stage telescopic
Lock type:	Toggle type
Leg material:	Alloy
Warranty:	3 Years

### OPTIONAL ACCESSORIES

390	MD pro dolly
391	LW pro dolly
550	Rubber feet (set of 3)
411	On ground spreader
508	Above ground spreader
835	Above ground spreader
378	D75 - D100 tripod bowl adapter



Quality  
ISO 9001

SAI GLOBAL

#### AUSTRALIA

Miller Camera Support Equipment  
30 Hotham Parade  
Artarmon, Sydney, NSW 2064  
Australia

P +61 2 9439 6377 F +61 2 9438 2819  
sales@miller.com.au

#### EUROPE

Miller Fluid Heads (Europe) Ltd.  
Unit 12A, Shepperton Business Park  
Govett Avenue, Shepperton  
Middlesex, TW17 8BA  
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211  
sales@millertripods-europe.com

#### USA

Miller Camera Support LLC  
216 Little Falls Road (Unit 15 & 16),  
Cedar Grove, New Jersey 07009  
USA

P +1 (973) 857 8300 F +1 (973) 857 8188  
sales@millertripods.us