

Low Cost Rackmount Keyboard Mouse Drawer

RACKMUX®

1RU PS/2 and USB keyboard drawers with touchpad mouse.

- Available in PS/2 and USB models.
- Designed to fit in a standard 19" rack/cabinet.
- Keyboard extends 14.63" from front of rack.
- Anti-rust chassis.
- Rugged steel construction with durable powder coat finish



RACKMUX-UKT-LC

- PS/2
- USB

The RACKMUX® Low Cost Rackmount Keyboard Mouse Drawer combines a PS/2 or USB keyboard and touchpad mouse in a space-saving 1RU industrial strength drawer.

Specifications

PS/2 Keyboard Drawer

- PS/2 keyboard integrated with touchpad.
- Compatible with all PS/2 computers.
- Built-in cursor keys and numeric keys.
- 104-key US layout keyboard.
- GlidePoint touchpad.
 - Usable surface dimension: 2.25x1.63"
- Travel distance: 4.0 ±0.5 mm
- Travel to peak: 1.5 ±0.5 mm
- Peak force: 50 ±10 gm
- Switch life: 10 million life cycles
- Electronic data: +5VDC ±5% @ 300mA

USB Keyboard Drawer

- USB keyboard integrated with touchpad.
- Compatible with USB PC computers.
- Built-in cursor keys and numeric keys.
- 104-key US layout keyboard.
- GlidePoint touchpad.
 - Usable surface dimension: 2.25x1.63"
- Travel distance: 4.0 ±0.5 mm
- Travel to peak: 1.5 ±0.5 mm
- Peak force: 50 ±10 gm
- Switch life: 10 million life cycles
- Electronic data: +5VDC ±5% @ 300mA
- Compatible with NTI's VGA USB KVM Switches: UNIMUX-USBV-2, UNIMUX-USBV-40, UNIMUX-USBV-4HD and UNIMUX-USBV-8HD

Dimensions

- WxDxH (in.): 17.32x13x1.75
- Keyboard extends 14.63" from front of rack.
 - Drawer does not lock into position when pulled out.
- Weight: 10.5 lbs (4.76 kg)

Environmental

- Operating temperature: 32 to 131°F (0 to 55°C).
- Storage temperature: -4 to 140°F (-20 to 60°C).
- Operating humidity: 10 to 95% RH.

Cables

- Keyboard/mouse proprietary cable.

Warranty

- Two years

Low Cost Rackmount Keyboard Mouse Drawer Models

NTI Part #	Description
RACKMUX-KT-LC	Low Cost PS/2 rackmount keyboard drawer
RACKMUX-UKT-LC	Low Cost USB rackmount keyboard drawer