MULTI VIEWER


4 CHANNEL 3G-SDI SCALING MULTI VIEWER




One or more inputs can be scaled and directed to the outputs in a variety of layouts. All inputs are resolution and frame rate independent. In addition, audio bars can be overlaid on each channel for quick signal monitoring. Text overlay can be customized for each input and as an additional feature input resolution display can be enabled or disabled.

The three parallel Outputs (2x 3G-SDI and 1x HDMI) support Up and Down Scaling and frame rate conversion.

MVS-3 can be configured via LAN. It also features external dip-switches for manual configuration.





MULTI VIEWER

Model: MVS-3

4x 3G-SDI to HDMI and SDI MULTI VIEWER WITH SCALING AND FRAME RATE CONVERSION

3G-SDI QUAD SPLIT MULTI-VIEWER

Technical Specifications

Input Video Formats SDI:


- 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- 1920x1080psf 23.98, 24, 25, 29.97, 30
- 1920x1080i 50, 59.94, 60
- 1280x720p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- PAL
- NTSC


Output Video Formats SDI, HDMI:


- 1920x1080p 24, 25, 29.97, 30, 50, 60
- 1920x1080i 50, 60
- 1280x720p 25, 30, 50, 60

Color Space and Precision:

Inputs: YUV or RGBOutputs: YUV







Video Inputs:

4x 3G-SDI, SMPTE 259/292/424, YCbCr 4:2:2

Video Outputs:

- HDMI 1.3a
- 2x 3G-SDI

Size:

• 5"x2.4.1"x0.95" (125.5x104x24.5mm)

Weight:

• 0.7lb (0.30kg)

Power:

12V 6W max

In the Box:

- Multi Viewer
- International Wall Power Supply
- Mounting Brackets

Warranty:

• 2 years

