SA752PU



Mounting Pattern 600 x 400mm (23.62" x 15.75")




SMARTMOUNT.

Articulating Wall Arm

FOR 37" TO 55" DISPLAYS

The SmartMount® Articulating Wall Arm series offers the most versatile installation features and mounting options. The I-Shaped Adaptor plate's innovative design helps avoid blocking connections on back of display. Vertical adjustment ability allows for post installation leveling, making it easier than ever to find the perfect display position. With SA752PU, extend the display up to 26.47" (672mm) or fully-retract it to just 2.97" (75mm) from the wall for the perfect viewing position. The display can now simply be installed by a single person with the Hook-and-Hang™ system. One-Touch™ tilt technology offers +15°/-5° vertical tilt movement for the ideal viewing angle. Integrated cable management protects, contains and conceals cables for a clean installation.

- Universal mount accommodates 200 x 100 to 600 x 400mm VESA® mounting patterns
- Retracts to hold display just 2.97" (75mm) from the wall
- ±90° of pivot allows for perfect display positioning
- Easy leveling ±5° after display installation
- Quick and easy, Hook-and-Hang™ one-person installation
- Landscape or portrait mounting options increases display versatility
- Single stud wall plate design increases electrical and cable management options
- Includes all necessary wall and display attachment hardware
- Design is UL listed and tested to four times stated load capacity





Swivel, tilt, extend or retract the display for the perfect viewing angle.



Integrated cable management keeps cords and cables out of the way.



Comes in color packaging with included installation hardware and easy to follow instructions.



Please visit peerless-av.com/en-us/patents for patent information.

SA752PU

SmartMount® Articulating Wall Arm for 37" to 55" Displays

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
SA752PU	24.50" x 17.46" x 2.97"-26.47" (622 x 444 x 75-672mm)	17.9lb (8.1kg)	90lb (41kg)	Scratch Resistant Fused Epoxy	Semi-Gloss Black

Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
SA752PU	29.25" x 19.00" x 4.25" (743 x 483 x 108mm)	22.7lb (10.3kg)	735029266563	Wall Mount, Wall and Display Installation Hardware, Installation Instructions	1

Accessories

ACCXT400: Recessed Power Outlet with Low Voltage In-Wall Cable Routing

IBA4-W: Easy Mount Recessed Low Voltage Cable Plate


IBA5-W: Recessed Low Voltage Media Plate with Duplex Surge Suppressor

WSP756: Metal Stud Wall Plate


All dimensions = inch (mm)




TOP VIEW



WALL PLATE DETAIL







SIDE VIEW EXTENDED +15°/-5° TILT

Architect Specifications

The SmartMount® Articulating Wall Arm shall be a Peerless-AV model SA752PU and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV 2300 White Oak Cir

2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500

Peerless-AV EMEA

Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom

+44 (0) 1923 200100 Fax: +44 (0) 1923 200101

Peerless-AV Latin America

Ave de las Industrias 413 Parque Industrial Escobedo Escobedo, N.L., Mexico 66062

+52 (81) 8384-8300 Fax: +52 (81) 8384-8360

